





Contents

01.	CRL Langle Office Partition Systems and Glazing Channels Single Glazed Office Partition System Double Glazed Office Partition System	
	Aluminium Glazing Profiles	
	Lift and Drop Profiles	1
	Clamping Profiles	2
	Shallow Profile Systems Office Partition System Accessories	2
	Glass Joints	2
	Glazing Blocks	2
02.	CRL Door Controls	2
02 .	Oil Dynamic Door Hardware	2
	Oil Dynamic Self-Closing Hinges	3
	Floor Mounted Door Closers	3
03.	CRL Patch Hardware	3
04.	CRL Door Rails and Side Rails	4
	Pivot Arms	5
	Lock Accessories	5
	Door Accessories	5
	Side Lite Rails	5
05.	CRL Handles and Locks	5
	Internal Glass Door Hinges	6
06.	CRL Sliding and Bi-Folding Doors	6
	Compact-X 70	6
	Compact-X 150	6
	Laguna Series	7
	Custom Bi-Folding Sliding Doors	7
07.	CRL Spider Fixings	7
	Regular Spider Fixings	7
	Heavy-Duty Spider Fixings	8
	Spider Fixing Brackets	8
08.	CRL Glass Awning Systems	9
	Awning Kit for Glass Canopy	9
	Awning Wall Mounted Brackets	9
	Awning Single Components	10
09.	CRL Structural Standoffs and Glass Clamps	10
	Langle Standoffs	10
	Heavy-Duty Standoffs	10
	Glass Clamp Cookets	11
	Glass Clamp Gaskets	11
10.	CRL Glazing Accessories Silicones	11
	Adhesives and Cleaners	11 11
	Lifters	12
	Glass Handling	12
	Glass Harlaling	12

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk w: crlaurence.co.uk





t: 00 800 0421 6144 **e:** crl@crlaurence.co.uk

CRL Langle Single Glazed Office Partition System

Glass-Partition-Wall-System

Office is a dry glazing system. It includes a frame and door frame system. A system easily assembled and installed producing maximum transparency.

Advantages

- No wet sealing necessary
- · Door hinge fully height-adjustable, no drilling and milling neccessary
- High sound reduction possible
- Matching frame profile for glass/glass and glass/wall
- Suitable for many common hinge and lock types
- Glass door 8 -12 mm
- Glass side part 8 16 mm

Applications


- Office glazings and glass partition walls
- Interior glazings for private homes
- Practices and chambers
- Hotels and spas
- · Smoking areas
























Door horizontal section



Door vertical section






2 30 4

Frame horizontal section



Frame vertical section

w: crlaurence co uk





Single Glazed Door Frame Profile Wall-to-Glass Door W

Includes: 1 x FBD6xx and 1 x FDJxx

- For 8 to 10mm glass
- For 12mm glass, order gaskets separately Cat. No. FFPBL see page 9

Cat. No. FW2GD1SA

1.1m length, Satin Anodised

Cat. No. FW2GD1BN 1.1m length, Metres, Brushed Nickel

Cat. No. FW2GD1MBL

1.1m length, Matte Black

Cat. No. FW2GD3SA 3m length, Satin Anodised

Cat. No. FW2GD3BN

3m length, Brushed Nickel

Cat. No. FW2GD3MBL

3m length, Matte Black

Single Glazed Door Frame Profile Glass-to-Glass

Door G

Includes: 1 x FBD6xx, 1 x FCLPD6xx, 1 x FDJxx, 1 x FRGxx and 1 x FFPxx

For 8 to 10mm glass

Cat. No. FG2GD1SA 1.1m length, Satin Anodised

Cat. No. FG2GD1BN

1.1m length, Brushed Nickel Cat. No. FG2GD1MBL

1.1m length, Matte Black

Cat. No. FG2GD3SA 3m length, Satin Anodised

Cat. No. FG2GD3BN

3m length, Brushed Nickel

Cat. No. FG2GD3MBL 3m length, Matte Black

Single Glazed Set for Wall-to-Glass Door Frame

Door W

Includes: 2 x 2450mm and 1 x 1100mm wall profiles with gaskets, 1 x FSP strike plate, 3 pair x FHHN hammer head nuts and 4 x FFCC corners

- For 8 to 10mm glass
- For 12mm glass, order gaskets separately Cat. No. FFPBL see page 9

Cat. No. FTW2GDSA Satin Anodised

Cat. No. FTW2GDBN

Brushed Nickel Cat. No. FTW2GDMBL



Single Glazed Set for Glass-to-Glass Door Frame

Door G

Includes: $2 \times 2450 \text{mm}$ and $1 \times 1100 \text{mm}$ wall profiles with gaskets, $1 \times FSP$ strike plate, 3 pair x FHHN hammer head nuts and 4 x FFCC corners

• For 8 to 10mm glass

Cat. No. FTG2GDSA

Cat. No. FTG2GDBN Brushed Nickel

Cat. No. FTG2GDSA Matte Black



Contact technical sales for details

Other RAL colours available on request



CRL Langle Single Glazed Office Partition System





Single Glazed Fixed Frame Profile for Ceiling

Top Frame W

Includes: 1 x FTPD6xx, 1 x FFPxx and 1 x FRGxx

For 8 to 10mm glass

Cat. No. FC2GF3SA 3m length Satin Anodised

Cat. No. FC2GF3BN

3m length, Brushed Nickel Cat. No. FC2GF3MBL

3m length, Matte Black



Includes: 1 x FRMD6xx, 1 x FCLPD6xx, 1 x FFPxx and 1 x FRGxx

• For 8 to 10mm glass

Cat. No. FW2GF3SA 3m length, Satin Anodised

Cat. No. FW2GF3BN 3m length, Brushed Nickel

Cat. No. FW2GF3MBL 3m length, Matte Black







Length: 6 metres

Gasket to be ordered separately

Cat. No. FTPD6SA

Cat. No. FTPD6BN

Cat. No. FTPD6MBL

Matte Black





Single Glazed Fixed Frame Profile for Floor, Wall and Ceiling

· Length: 6 metres

· Gasket and clip profile set to be ordered separately

Cat. No. FRMD6SA

Satin Anodised

Cat. No. FRMD6BN Brushed Nickel

Cat. No. FRMD6MBL

Matte Black





Single Glazed Door Frame Profile

• Length: 6 metres

· Gasket to be ordered separately


Cat. No. FBD6SA

Satin Anodised

Cat. No. FBD6BN Brushed Nickel

Cat. No. FBD6MBL

Matte Black





• Length: 6 metres

Cat. No. FCLPD6SA

Satin Anodised

Cat. No. FCLPD6BN

Cat. No. FCLPD6MBL





Single Glazed Door Jamb Gasket for 8 to 10mm Glass

• EPDM rubber

Cat. No. FDJBL 50m roll length, Black

Cat. No. FDJGR

50m roll length, Grey Cat. No. FDJBL6 6m roll length, Black

Cat. No. FDJGR6

6m roll length, Grey

Cat. No. FRGBL

50m roll length, Black

Single Glazed Roll-In Fixing Gasket for 8 to 16mm glass EPDM rubber

Cat. No. FRGGR

50m roll length, Grey

Cat. No. FRGBL6 6m roll length, Black

Cat. No. FRGGR6 6m roll length, Grey

Single Glazed Fixed Profile Gasket for 8, 10 and 12mm Glass

EPDM rubber



Cat. No. FFPBL 50m roll length, Black

Cat. No. FFPGR 50m roll length, Grey

Cat. No. FFPBL6

6m length Black Cat. No. FFPGR6

6m length, Grey

Single Glazed Fixed Profile Gasket for 16mm Glass

• 50m roll length

• EPDM rubber


Cat. No. FFP16BL Black

Cat. No. FFP16GR



t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk

CRL Langle Single Glazed Office Partition System



Single Glazed Hammer Head Nut for 8 to 10mm Glass

• Includes countersunk screw with coating

- Cat. No. FHHN

 Use 1 pair for one hinge

 Use 1 pair for one striking plate





Single Glazed hammer Head Nut for 12mm Glass

• Includes countersunk screw with coating







Single Glazed Striking Plate

Cat. No. FSP




10



Single Glazed Striking Plate

Cat. No. FDSP





Single Glazed Floor and Corner Connector

Includes setscrew

Cat. No. FFCC

• Use 1 each for one corner






Single Glazed Top frame and frame Connector

Includes setscrews

Cat. No. FFCCL






Single Glazed T-Connector

Includes setscrews

Cat. No. FTC

11





t: 00 800 0421 6144 **e:** crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk

CRL Langle Double Glazed Office Partition System NEW

Glass-Partition-Wall-System

Office is a dry glazing system. It includes a frame and door frame system. A system easily assembled and installed producing maximum transparency.

Advantages

- No wet sealing necessary
- Door hinge fully height-adjustable, no drilling and milling neccessary
- Can be executed as single or double glazing
- High sound reduction possible
- Matching frame profile for glass/glass and glass/wall
- Suitable for many common hinge and lock types
- Glass door 10-12 mm
- Wood door 40 mm

12

• Glass side part 20-28 mm

Applications

- Office glazings and glass partition walls
- Interior glazings for private homes
- Practices and chambers
- · Hotels and spas
- · Smoking areas
























Horizontal section Basis XL/Frame XL




4

Horizontal section Frame XL/Frame T XL



Vertical section Basis XL/ Frame XL





Double Glazed Door Frame Profile Wall-to-Glass

Door XL

Includes: 1 x FXBD6xx, 1 x FXCLPD6xx and 1 x FXDJxx • For 10 to 12mm glass or 40mm thick wood doors



Cat. No FXW2GD1MBL 1.1m length, Matte Black Cat. No. FXW2GD3SA

Cat. No. FXW2GD1SA

1.1m length, Satin Anodised Cat. No. FXW2GD1BN

1.1m length, Brushed Nickel

Cat. No. FXW2GD3BN 3m length, Brushed Nickel

Cat. No FXW2GD3MBL 3m length, Matte Black

Double Glazed Door Frame Profile Glass-to-Glass

Door XL

Includes: 1 x FXBD6xx, 1 x FXCLPD6xx, 1 x FXDJxx, 1 x FFPxx, 1 x FFP14xx and 1 x FRGxx

• For 10 to 12mm glass or 40mm thick wood doors



Cat. No. FXG2GD1SA 1.1m length, Satin Anodised

Cat. No. FXG2GD1BN 1.1m length, Brushed Nickel

Cat. No. FXG2GD1MBL 1.1m length, Matte Black

Cat. No. FXG2GD3SA

3m length, Satin Anodised

Cat. No. FXG2GD3BN 3m length, Brushed Nickel

Cat. No. FXG2GD3MBL

3m length, Matte Black

Double Glazed Fixed Frame Profile for Floor, Wall and Ceiling

Frame XL

Includes: 1 x FXFRMD6xx, 1 x FCLPD6xx, 1 x FFPxx, 1 x FFP14xx and 1 x FRGxx

• For 10 to 12mm glass or 20 to 28mm double glazed units

Cat. No. FXW2GF3SA

3m length, Satin Anodised

Cat. No. FXW2GF3BN 3m length, Brushed Nickel

Cat. No FXW2GF3MBL 3m length, Matte Black

Double Glazed Fixed Frame Profile for Ceiling

Top Frame XL

Includes: 1 x FXTPD6xx, 1 x FFPxx, 1 x FFP14xx and 1 x FRGxx

• For 10 to 12mm glass or 20 to 28mm double glazed units

Cat. No. FXC2GF3SA 3m length, Satin Anodised

Cat. No. FXC2GF3BN 3m length, Brushed Nickel

Cat. No FXC2GF3MBL



Double Glazed Door Frame Profile Glass-to-Glass

Includes: 1 x FXFRMT6xx, 2 x FCLPD6xx, 1 x FFPxx, 1 x FFP14xx and FRGxx

• For 20 to 28mm double glazed units



Cat. No. FXG2GF3SA

3m length, Satin Anodised Cat. No. FXG2GF3BN

3m length. Brushed Nickel

Cat. No FXG2GF3MBL 3m length, Matte Black





Other RAL colours available on request





t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence co uk

CRL Langle Double Glazed Office Partition System NEW



Double Glazed Door Profile

- · Length: 6 metres
- · Gasket to be ordered separately



Cat. No. FXBD6SA

Satin Anodised


Cat. No. FXBD6BN

Cat. No. FXBD6MBL



Clip Profile

• Length: 6 metres



Cat. No. FCLPD6SA

Satin Anodised

Cat. No. FCLPD6BN Brushed Nickel

Cat. No. FCLPD6MBL

Matte Black



Door Profile Filler Strip

• Length: 6 metres



Cat. No. FXCLPD6SA

Cat. No. FXCLPD6BN

Brushed Nickel

Cat. No. FXBD6MBL



Double Glazed Base Profile



- · Length: 6 metres



- · Gasket to be ordered separately



- - Cat. No. FXFRMD6BN

Cat. No. FXFRMD6MBL

Cat. No. FXFRMD6SA

Matte Black



Double Glazed Inline Profile

- · Length: 6 metres
- · Gasket to be ordered separately



Cat. No. FXFRMT6SA

Cat. No. FXFRMT6BN


Cat. No. FXFRMT6MBL Matte Black



14

Double Glazed Ceiling Top Fixed Frame Profile

- Length: 6 metres
- · Gasket to be ordered separately





Cat. No. FXTPD6SA

Cat. No. FXTPD6MBL







• EPDM rubber



EPDM rubber



Cat. No. FXDJBL

Cat. No. FXDJGR

50m roll length, Grey Cat. No. FXDJBL6

6m length, Black Cat. No. FXDJGR6 6m length, Grey

Cat. No. FFPGR

Cat. No. FFPBL6

6m length, Black Cat. No. FFPGR6

6m length, Grey



Cat. No. FFP14BL 50m roll length, Black Cat. No. FFP14GR 50m roll length, Grey Cat. No. FFP14BL6

6m length, Black Cat. No. FFP14GR6

6m length, Grey



Double Glazed Fixed Profile Gasket for 28mm Glass

- 50m roll length
- EPDM rubber

Cat. No. FFP16BL Cat. No. FFP16GR

50m roll length, Grey

Cat. No. FRGBL


Roll-In Fixing Gasket for 8 to 16mm Glass



EPDM rubber


50m roll length, Black Cat. No FRGGR 50m roll length, Grey Cat. No. FRGBL6

6m length, Black Cat. No. FRGGR6 6m length, Grey




Double Glazed Hammer Head Nut Cat. No. FXHHN

• For 10 to 12mm glass



Double Glazed 90° Connector for Floor and Ceiling Profiles

Cat. No. FXCH



Double Glazed Z Connector Cat. No. FXCZ





Double Glazed Support Plate for Dorma Hinge


15

Cat. No. FXCU

• For 10 to 12mm glass

t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk

CRL Langle Double Glazed Office Partition System NEW



Double Glazed Striking Plate


Cat. No. FXDSP





Cat. No. FFCC





Double Glazed Striking Plate

Cat. No. FXSP





Double Glazed Frame and Top Frame or Basis Connector

Cat. No. FFCCL






Airborne sound insulation to EN ISO 10140



SETUP A

Glass door including drop-down seal with glass side panels and fanlight



SETUP B

Wooden sound-proof door including drop-down seal with glass side panels and fanlight



16

SETUP C

Fixed glazing




The achievable sound insulation value depends on the glass thickness, glass construction (in case of installed double glazing), connection to the structure, as well as on the building acoustic properties of the flanking building parts. We will be pleased to advise you personally.

NOTE: dB is decibel level achieved





CRL Lift and Drop Profiles





25mm Deep Wet/Dry Glaze U-Channel

- Available in 3 or 6m stock lengths
- Use monolithic tempered glass
- Typically used at the bottom and sides of the glass
- Use with silicone (wet) or glazing gasket (dry)
- · Matching end caps sold separately
- · Gasket to be ordered separately
- . For 10 or 12mm glass

Cat. No. WU3BSASL

3m Length,

Brushed Stainless Anodised Cat. No. WU3BASL

3m Length, Bright Anodised

Cat. No. WU3SASL

6m Length, Brushed Stainless Anodised Cat. No. WU3BA240 6m Length, Bright Anodised Cat. No. WU3SA240

6m length, Satin Anodised

Cat. No. WU3BSA240





38mm Deep Wet/Dry Glaze U-Channel

- 38mm height
- Available in 3 or 6m stock lengths
- Use monolithic tempered glass
- Typically used at the top of the glass
- Use with silicone (wet) or glazing gasket (dry)
- · Matching end caps sold separately
- Gasket to be ordered separately • For 10 or 12mm glass

Cat. No. WU1BSASL 3m Length, Brushed Stainless Anodised

Cat. No. WU1BASL 3m Length, Bright Anodised

Cat. No. WU1SASL 3m Length, Satin Anodised

Cat. No. WU1BSA240 6m Length,


Brushed Stainless Anodised Cat. No. WU1BA240

6m Length, Bright Anodised

Cat. No. WU1SA240

6m length, Satin Anodised





51mm Deep Wet/Dry Glaze U-Channel

- 51mm height
- · Available in 3 or 6m stock lengths
- Use monolithic tempered glass
- . Typically used at the top of the glass
- Use with silicone (wet) or glazing gasket (dry)
- · Matching end caps sold separately
- · Gasket to be ordered separately
- . For 10 or 12mm glass

Cat. No. WU2BSASL 3m Length,

Brushed Stainless Anodised

Cat. No. WU2BASL

3m Length, Bright Anodised

Cat. No. WU2SASL 3m Length, Satin Anodised Cat. No. WU2BSA240 6m Length,

Brushed Stainless Anodised

Cat. No. WU2BA240 6m Length, Bright Anodised

Cat. No. WU2SA240 6m length, Satin Anodised



End Cap for Wet/Dry U-Channel

- Finishes off exposed ends
- Easy-to-install with silicone sealant
- Six standard architectural finishes, with custom finishes available

25mm height, Brushed Stainless Anodised

Cat. No. WU3ECBA

Cat. No. WU3ECBSA

25mm height, Bright Anodised

Cat. No. WU3ECSA

25mm height, Satin Anodised

Cat. No. WU1ECBSA

38mm height, Brushed Stainless Anodised

Cat. No. WU1ECBA

38mm height, Bright Anodised Cat. No. WU1ECSA

38mm height, Satin Anodised

Cat. No. WU2ECBSA

51mm height,

Brushed Stainless Anodised Cat. No. WU2ECBA

51mm height, Bright Anodised

Cat. No. WU2ECSA 51mm height, Satin Anodised



Black and Grey Roll-In Gasket

- Eliminates the need for silicone
- Can be used with all finishes of our wet/dry U-Channel.
- For use with WU3, WU1, WU2 channel
- . For 10 and 12mm glass

Cat. No. RG38100

10mm Glass, 30m Length Roll, Black

Cat. No. RG38500

10mm Glass, 152.4m Length Roll, Black

Cat. No. RG12100

12mm Glass, 30m Length Roll, Black

Cat. No. RG12500

12mm Glass, 152.4m Length Roll, Black

Cat. No. RGG38100

10mm Glass, 30m Length Roll, Grey

Cat. No. RGG12100


12mm Glass, 30m Length Roll, Grey




door hardware and office partition systems 18 t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence co uk

CRL Clamping Profiles


AVAILABLE IN BRUSHED NICKEL AND SATIN ANODISED FINISHES








For 10mm glass



For 12mm glass



For 12.8mm glass



4m Clamping Profile

- Includes L-shaped channel, cladding, gaskets and glass spacers
- Sold in 4m lengths

20

• For 8, 10, 12 and 12.8mm toughened glass

Cat. No. EUMB8BN

8mm Glass, Brushed Nickel

Cat. No. EUMB8SA

8 mm Glass, Satin Anodised

Cat. No. EUMB8BA

8mm Glass, Bright Anodised

Cat. No. EUMB10BN

10mm Glass, Brushed Nickel Cat. No. EUMB10SA

10mm Glass, Satin Anodised

Cat. No. EUMB10BA 10mm Glass, Bright Anodised

Cat. No. EUMB12BA

12mm Glass, Bright Anodised

Cat. No. EUMB128BA 12.8mm Glass, Bright Anodised

Cat. No. EUMB12BN

12mm Glass, Brushed Nickel Cat. No. EUMB12SA

12mm Glass, Satin Anodised

Cat. No. EUMB128BN 12.8mm Glass, Brushed Nickel

Cat. No. EUMB128SA

12.8mm Glass, Satin Anodised

CRL Shallow Profile Systems



Shallow U-Channel with Top Load Roll-in Glazing Gasket

- Gasket included for 12mm glass
- Ideal for recessed 'all-glass' installations
- Ready-to-ship models from CRL inventory
- Nine standard architectural finishes see crlaurence.co.uk
- Custom finishes and powder painting available
- 3m length
- For 10 and 12mm glass

Cat. No. SCBS3812SL

Cat. No. SCBA3812SL Bright Anodised

Cat. No. SCSA3812SL Satin Anodised





Regular U-Channel with Top Load Roll-In Glazing Gasket

- Gasket included for 12mm glass
- Ideal for ceiling or floor installations
- · Ready-to-ship models from crl inventory
- Nine standard architectural finishes see crlaurence.co.uk
- · Custom finishes and powder painting available
- 3m length
- For 10 and 12mm glass

Cat. No. UCBS3812SL **Brushed Stainless**

Cat. No. UCBA3812SL

Cat. No. UCSA3812SL



Shallow U-Channel End Caps

- Several finishes available to match our u-channels
- For use with our shallow u-channel 'SC' series see above

Cat. No. SCECBS

Brushed Stainless

Cat. No. SCECBA Bright Anodised

Cat. No. SCECSA



Regular U-Channel End Caps

- Several finishes available to match our u-channels
- For use with our regular u-channels 'UC' series see above

Cat. No. UCECBS Brushed Stainless

Cat. No. UCECBA Bright Anodised

Cat. No. UCECSA

Satin Anodised



Roll-In EPDM Gaskets for Sidelite Rails

· Dry glaze push-in top load glazing gasket

Cat. No. GG38100 10mm Glass, 30.5m Roll

Cat. No. GG38500 10mm Glass, 152.4m Roll

Cat. No. GG12100

12mm Glass, 30.5m Roll

Cat. No. GG12500

12mm Glass, 152.4m Roll



Aluminium Neoprene Setting Block for Glass

- Protects glass edge while providing rigid glass support in sidelite rails and U-channel
- Provides proper height for recommended glass coverage
- For use with our regular u-channels 'UC' series see above

Cat. No. UCSB4

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems

CRL Langle Office Partition System Accessories NEW



Square Hinge Cat. No. FHSSA Satin Anodised

Cat. No. FHSBN

Cat. No. FHSMBL



- 50kg max weight
- 1000mm max door width
- 2200mm max door height with 2 hinges
- 2600mm max door height with 3 hinges
- For 8 to 10mm glass



D-Hinge

Cat. No. FHDSA

Cat. No. FHDBN

Cat. No. FHDMBL



- 50kg max weight
- 1000mm max door width
- 2200mm max door height with 2 hinges
- 2600mm max door height with 3 hinges
- For 8 to 10mm glass



Square Latch with Cylinder

Cat. No. FLKSSA

Cat. No. FLKSBN

Cat. No. FLKSMBL Matte Black

Also available as a set which includes the square latch, 2 square hinges and handle set:

FLKSSASET FLKSBNSET FLKSMBLSET




D-Latch with Cylinder

Cat. No. FLKDSA

Cat. No. FLKDBN





FI KDSASET FLKDBNSET



Square Latch Non-Locking

Cat. No. FLSSA

Cat. No. FLSBN

Cat. No. FLSMBL






FLSSASET FLSMBLSET



D-Latch Non-Locking

Cat. No. FLDSA

Cat. No. FLDBN



Also available as a set which includes the D-latch, 2 D-hinges and handle set:

FLDSASET



22

Handle Set

Cat. No. FLHMTSA

Cat. No. FLHMTBN

Cat. No. FLHMTMBL



Installation Key

Cat. No. EU0KEY



CRL Glass Joints





Clear Glass Joint System 180° Partition Strip

- Provides a clear slimline finish between two glass panels
- Excellent adhesion from pre-applied high bond tape
- 3m lengths

Cat. No. EZCC88 8.8mm, Laminated Glass

Cat. No. EZCC10 10mm, Toughened Glass

Cat. No. EZCC108 10.8mm, Laminated Glass

Cat. No. EZCC12 12mm, Toughened Glass

Cat. No. EZCC128 12.8mm, Laminated Glass

Cat. No EZCC168 16.8mm, Laminated Glass



Clear Glass Joint System 90° Corner Protection Strip

- Provides a clear slimline finish between two glass panels
- Excellent adhesion from pre-applied high bond tape
- 3m lengths

Cat. No. EZCL10 10mm, Toughened Glass

Cat. No. EZCL108 10.8mm. Laminated Glass

Cat. No. EZCL12 12mm, Toughened Glass

Cat. No. EZCL128

12.8mm, Laminated Glass

Cat. No. EZCT10

10mm, Toughened Glass

Cat. No. EZCT108

10.8mm, Laminated Glass



Clear Glass Joint System 3-Way Partition Strip

- Provides a clear slimline finish between two glass panels
- Excellent adhesion from pre-applied high bond tape





Cat. No. EZCT12 12mm, Toughened Glass

Cat. No. EZCT128

12.8mm, Laminated Glass

Cat. No. EZCE10

10mm, Toughened Glass

Cat. No. EZCE108

Cat. No. EZCE12

10.8mm, Laminated Glass





Clear Glass Joint System Abutment Strip

- Provides a clear slimline finish between two glass panels
- Excellent adhesion from pre-applied high bond tape
- 3m lengths



12.8mm, Laminated Glass





CRL Glass Joints





Clear Glass Joint System 180° In-Line 2-Way Partition Strip

- · Clips over the glass joint
- 3m lengths
- Does not feature clear high bond tape

Cat. No. CL0N10 10mm, Toughened Glass

Cat. No. CL0N108

10.8mm, Laminated Glass

Cat. No. CL0N12 12mm, Toughened Glass

Cat. No CL0N128 12.8mm, Laminated Glass





Clear Glass Joint System 90° 2-Way Partition Strip

- · Clips over the glass joint
- Excellent adhesion from pre-applied clear high bond tape

Cat. No. CL0N210 10mm, Toughened Glass

Cat. No. CL0N2108 10.8mm, Laminated Glass

Cat. No. CL0N212 12mm, Toughened Glass

Cat. No. CL0N2128 12.8mm, Laminated Glass





Clear Glass Joint System 90° 3-Way Partition Strip

- · Clips over the glass joint
- Excellent adhesion from pre-applied clear high bond tape

Cat. No. CL0N310 10mm, Toughened Glass

Cat. No. CL0N3108 10.8mm, Laminated Glass

Cat. No. CL0N312

12mm, Toughened Glass

Cat. No. CL0N3128

12.8mm, Laminated Glass





Clear Glass Joint System 135° 2-Way Partition Strip

- Clips over the glass joint
- Excellent adhesion from pre-applied clear high bond tape

Cat. No. CL0N410 10mm, Toughened Glass

Cat. No. CL0N4108

10.8mm, Laminated Glass

Cat. No. CL0N412 12mm, Toughened Glass

Cat. No. CL0N4128 12.8mm, Laminated Glass



Ratchet Tensioning Kit with two Vacuum lifters

- Ideal for countertops, marble, granite, flooring, mirrors and glass
- Comes with two 203mm vacuum lifters
- Uses S108 vacuum lifter mounting points
- Carrying capacity is 147kg

Cat. No. G0284

• Pulls with tremendous force





CRL Glazing Blocks

Plastic Glazing Blocks Cat. No. KK201 • 100 x 20 x 1mm • Spacers • Polypropylene • 1000 per unit	Plastic Glazing Blocks Cat. No. KK202 • 100 x 20 x 2mm • Spacers • Polypropylene • 1000 per unit	
Plastic Glazing Blocks Cat. No. KK203 • 100 x 20 x 3mm • Spacers • Polypropylene • 1000 per unit	Plastic Glazing Blocks Cat. No. KK204 • 100 x 20 x 4mm • Spacers • Polypropylene • 1000 per unit	
Plastic Glazing Blocks Cat. No. KK205 • 100 x 20 x 5mm • Spacers • Polypropylene • 1000 per unit	Plastic Glazing Blocks Cat. No. KK206 • 100 x 20 x 6mm • Spacers • Polypropylene • 1000 per unit	
Wood Glazing Blocks Cat. No. KH202 • 80 x 20 x 2mm • Spacers • Impregnated wood • 100 per unit	Wood Glazing Blocks Cat. No. KH203 • 80 x 20 x 3mm • Spacers • Impregnated wood • 100 per unit	
Wood Glazing Blocks Cat. No. KH204 • 80 x 20 x 4mm • Spacers • Impregnated wood • 100 per unit	Wood Glazing Blocks Cat. No. KH205 • 80 x 20 x 5mm • Spacers • Impregnated wood • 100 per unit	
Wood Glazing Blocks Cat. No. KH206 • 80 x 20 x 6mm • Spacers • Impregnated wood • 100 per unit		

25

For Silicone see page 118


24



CRL Door Controls

In this section you will find CRL's best selection of hardware to control the closing speed of self-closing glass doors.

It includes oil dynamic door hardware, such as patch fittings and floor closers as well as oil dynamic hinges which have adjustable closing speed and offer a great alternative to floor closers and patch fittings.



t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk w: crlaurence.co.uk





Hydraulic Patch Fittings With Backcheck NEW

- Includes two adjustment screws to adjust the latching speed and the swing speed
- For interior use only
- Glass fabrication required
- 100kg max door weight
- 1000mm max door width

• For 8 to 12mm glass

Cat. No. CRL380BS No Hold Open, Brushed Stainless

Cat. No. CRL380PS No Hold Open, Polished Stainless

Cat. No. CRL380MBL No Hold Open, Matte Black

Cat. No. CRL380HBS Hold Open, Brushed Stainless

Cat. No. CRL380HBS Hold Open, Polished Stainless

Cat. No. CRL380HMBL Hold Open, Matte Black

Cat. No. PH21ABS Brushed Stainless Cat. No. PH21APS

Polished Stainless

Cat. No. PH21AMBL Matte Black



Door Patch Fitting With Insert

- 65mm pivot setback
- 80kg max door weight • 1100mm max door width
- 2740mm max door height
- For 10 to 12mm glass

Centre-Hung Free Swinging Top Pivot

• Surface mount top pivot for use with patch fittings and WEDGE-LOCK® Door Rail System - see page 50

w: crlaurence.co.uk

• Installs easily to wood or metal substrates

Cat. No. 1NT401

Centre-Hung Free Swinging Top Pivot





Oil Dynamic Patch Fitting Door Hinge

- · Closing speed can be adjusted
- Swings in and out a full 90 degrees, with stops at 0° , $+90^{\circ}$, and -90° .
- 100kg max door weight
- 1000mm max door width
- For 10 to 13.52mm glass
- Matching top patch fittings available

Cat. No. H100E10

Patch Fitting with Back Check, Hold Open

Cat. No. H100E10NF

Patch Fitting with No Back Check, Hold Open

Cat. No. H100E10NH0

Patch Fitting with Back Check, No Hold Open



Cat. No. H100E20





Top Patch Fitting

- 100kg max door weight
- 1000mm max door width
- For 8 to 13.52mm glass
- 12mm diameter pivot insert
- For use with H100E10 Oil Dynamic Patch Fitting
- For use with H100EP1V Top Pivot Plate







Patch Fitting Cover Plate for H100E10 and H100E20

Cat. No. H100ECBS **Brushed Stainless**

Cat. No. H100ECPS Polished Stainless

Cat. No. H100ECSA Satin Anodised

Cat. No. H100EC0RB Oil Rubbed Bronze

Replacement Screw Cover for H100E10

Cat. No. H100EBC



Top Pivot Plate for H100E20

- 12mm diameter top pivot pin
- For use used with H100E20



Cat. No. H100EP1V



28

CRL Oil Dynamic Self-Closing Hinges



Oil Dynamic Full Back Plate Wall to Glass Hinge,

- Swings in and out a full 90°, with stops at 0° , $+90^{\circ}$, and -90°
- 100kg max weight
- 1000mm max door width

Cat. No. H8010CH

Wall-to-Glass Hinge, Chrome

Cat. No. H8010SA

Wall-to-Glass Hinge, Satin Anodised

Cat. No. H8010SN

Wall-to-Glass Hinge, Satin Nickel

Wall-to-Glass Hinge, Chrome

Cat. No. H8010BTSA*

Wall-to-Glass Hinge, Satin Anodised

Cat. No. H8010BTSN*

Wall-to-Glass Hinge, Satin Nickel

Cat. No. H8010JCBS

Brushed Stainless

Polished Stainless

*Suitable for a damp/humid environment

Oil Dynamic Full Back Plate Wall to Glass Hinge,

No Hold Option · Adjustable closing speed, self-closing

Swings in and out a full 90°,

- 100kg max weight
- . 1000mm max door width
- For 8 to 13.52mm glass

Wall-to-Glass Hinge, Chrome

Cat. No. H8210SA

Wall-to-Glass Hinge, Satin Anodised

Cat. No. H8210SN

Wall-to-Glass Hinge, Satin Nickel

Wall-to-Glass Hinge, Chrome

Cat. No. H8210BTSA*

Wall-to-Glass Hinge, Satin Anodised

Cat. No. H8210BTSN*

Wall-to-Glass Hinge, Satin Nickel

*Suitable for a damp/humid environment

Oil Dynamic Offset Back Plate Wall to Glass Hinge,



Adjustable closing speed, self-closing

- Swings in and out a full 90° , with stops at 0° , $+90^{\circ}$, and -90° 100kg max weight
- · 1000mm max door width
- For 8 to 13.52mm glass

Cat. No. H8011CH

Offset Wall-to-Glass Hinge, Chrome

Cat. No. H8011SA

Offset Wall-to-Glass Hinge, Satin Anodised

Offset Wall-to-Glass Hinge, Satin Nickel

Offset Wall-to-Glass Hinge, Chrome

Cat. No. H8011BTSA*

Offset Wall-to-Glass Hinge, Satin Anodised

Cat. No. H8011BTSN*

*Suitable for a damp/humid environment

No Hold Option

Oil Dynamic Offset Back Plate Wall to Glass Hinge,



Adjustable closing speed, self-closing

- 100kg max weight
- 1000mm max door width
- For 8 to 13.52mm glass

Cat. No. H8211CH Wall-to-Glass Hinge, Chrome

Cat. No. H8211SA

Wall-to-Glass Hinge, Satin Anodised

Wall-to-Glass Hinge, Satin Nickel

Cat. No. H8211BTCH*

Cat. No. H8211BTSA*

Wall-to-Glass Hinge, Satin Anodised

Cat. No. H8211BTSN*

Wall-to-Glass Hinge, Satin Nickel

*Suitable for a damp/humid environment











- · 80kg max weight
- For 8 to 13.52mm glass



- · Adjustable closing speed, self-closing
- Swings in and out a full 90° , with stops at 0° , $+90^{\circ}$, and -90° .
- · 1000mm max door width



Cat. No. H8015CH Glass-to-Glass Hinge, Chrome

Cat. No. H8015SA

Glass-to-Glass Hinge, Satin Anodised

Cat. No. H8015SN

Glass-to-Glass Hinge, Satin Nickel

Cat. No. H8015BTCH* Glass-to-Glass Hinge, Chrome

Cat. No. H8015BTSA*

Glass-to-Glass Hinge, Satin Anodised

Cat. No. H8015BTSN* Glass-to-Glass Hinge, Satin Nickel

Cat. No. H8015JCBS

Adjustable Glass-to-Glass, Clad Option, Brushed Stainless

Cat. No. H8015JCPS

Adjustable Glass-to-Glass, Clad Option, Polished Stainless

*Suitable for a damp/humid environment

Cat. No. H8215CH

Glass-to-Glass Hinge, Chrome

Cat. No. H8215SA

Glass-to-Glass Hinge, Satin Anodised

Cat. No. H8215SN Glass-to-Glass Hinge, Satin Nickel

Cat. No. H8215BTCH*

Glass-to-Glass Hinge, Chrome

Cat. No. H8215BTSA*

Glass-to-Glass Hinge, Satin Anodised

Cat. No. H8215BTSN*

Glass-to-Glass Hinge, Satin Nickel *Suitable for a damp/humid environment

Cat. No. H8060CH Wall-to-Glass Rebated Hinge, Chrome

Cat. No. H8060SA

Wall-to-Glass Rebated Hinge, Satin Anodised

Cat. No. H8060BTCH*

Cat. No. H8060BTSA*

Cat. No. H8060BTSN*

Wall-to-Glass Rebated Hinge, Satin Nickel

*Suitable for a damp/humid environment

- Adjustable closing speed, self-closing
- Swings out 90 degrees
- Stops at 90 degrees
- 100kg max weight
- Cat. No. H8260SA Wall-to-Glass Rebated Hinge, Satin Anodised

Cat. No. H8260SN

Wall-to-Glass Rehated Hinge, Satin Nickel

Cat. No. H8260BTCH*

Cat. No. H8260CH Wall-to-Glass Rebated Hinge, Chrome

Wall-to-Glass Rebated Hinge, Chrome

Cat. No. H8260BTSA*

Wall-to-Glass Rebated Hinge, Satin Anodised

Cat. No. H8260BTSN* Wall-to-Glass Rebated Hinge, Satin Nickel *Suitable for a damp/humid environment









· Adjustable closing speed, self-closing

- For 8 to 13.52mm glass

Cat. No. H8010BTCH*

Adjustable Wall-to-Glass Hinge, Clad Option,

Cat. No. H8010JCPS

Adjustable Wall-to-Glass Hinge, Clad Option,

Cat. No. H8210CH

Cat. No. H8210BTCH*

Cat. No. H8011SN

Cat. No. H8011BTCH*

Offset Wall-to-Glass Hinge, Satin Nickel

Cat. No. H8211SN

Wall-to-Glass Hinge, Chrome





Oil Dynamic Glass to Glass Hinge, No Hold Option · Adjustable closing speed, self-closing Swings in and out a full 90°

· 1000mm max door width • For 8 to 13.52mm glass

80kg max weight



- Oil Dynamic Rebated Wall to Glass Hinge, Hold open · Adjustable closing speed, self-closing
- · For use with rebated door frames Swings out 90 degrees
- Stops at 90 degrees 100kg max weight · 1000mm max door width

For 10 to 12mm glass



Cat. No. H8060SN Wall-to-Glass Rebated Hinge, Satin Nickel

Wall-to-Glass Rebated Hinge, Chrome

Wall-to-Glass Rebated Hinge, Satin Anodised



Oil Dynamic Rebated Wall to Glass Hinge, No Hold Option

- . For use with rehated door frames
- 1000mm max door width • For 10 to 12mm glass



door hardware and office partition systems



30

CRL Floor Mounted Door Closers



Adjustable Power Narrow Width Floor Mounted Closer

- The perfect door closer to support CRL's patch hardware
- Interchangeable Spindle Heights
- 120kg max weight
- 1067mm max door width
- Adjustable power EN1 to EN4
- Complete with cement box, brushed stainless cover plate and spindle
- Coffin box EUCRL8460C0F can be used with this door closer (see below)
- Cover plate EUCRL84VLCPBS must be used with EUCRL8460C0F Coffin box (see below)

BEST SELLING FLOOR SPRING

Cat. No. EUCRL8460V 180° Hold Open

Cat. No. EUCRL8462V

180° No Hold Open

Cat. No. EUCRL8466V 105° Hold Open

NON-ADJUSTABLE OPTION AVAILABLE CRL8460

VARIABLE **CLOSING SPEED**

> VARIABLE **POWER**

INCLUDES BRUSHED STAINLESS COVER PLATE

OPTIONS

32



EUCRL84 Series Floor Closer Cover Plate

Cat. No. EUCRL84VC0VPS

Variable Cover Plate, Polished Stainless

Cat. No. EUCRL84VLCPBS 1.2mm Thick Cover Plate for EUCRL8460C0F

- For use with coffin box

Coffin Box for EUCRL8400V Series Floor Closers

Cat. No. EUCRL8460C0F



Interchangeable Floor Closer Spindles

- For use with CRL floor mounted closers
- For use with DORMA® BTS75 Series floor mounted door closer
- For use with Jackson® 900 Series floor mounted door closer
- Seven available heights from 3 to 33mm
- Flat tapered type
- For use with all CRL floor springs

Cat. No. CRL9040S3

3mm Collar Height Tapered

Cat. No. CRL9040S8 8mm Collar Height Tapered

Cat. No. CRL9040S13

Cat. No. CRL9040S18 18mm Collar Height Tapered

Cat. No. CRL9040S23

23mm Collar Height Tapered CAT. NO. CRL9040S28

28mm Collar Height Tapered

Cat. No. CRL9040S33

33mm Collar Height Tapered

CRL Dorma® Floor Mounted Door Closer



Dorma® BTS75 Series Floor Mounted Door Closer

- Adjustable spring power 1-4
- Complete with spindle
- 118kg max weights
- 1067mm max door width
- 90° hold open
- ANSI A156.4 Grade 1
- Standard and A.D.A compliant barrier-free openings
- Barrier free
- Cover to be purchased separately
- 25 years warranty

Cat. No. 31DBTS75V90H0

Cat. No. 31DBTS75V

VARIABLE **CLOSING SPEED**

VARIABLE **POWER**

OPTIONS

Dorma® BTS75V Floor Closer Cover Plate

- Brushed Stainless Steel finish
- For use with Dorma® BTS75 Floor mounted door closer

Cat. No. 31DBTS75VC0VBS

Cat. No. 31DBTS75VC0VPS



Interchangeable Floor Closer Spindles

- For use iwth CRL floor mounted closers
- For use with DORMA® BTS75 Series floor mounted door closer
- For use with Jackson® 900 Series floor mounted door closer
- Seven available heights from 3 to 33mm
- Flat tapered type
- For use with all CRL floor springs



8mm Collar Height Tapered Cat. No. CRL9040S13

13mm Collar Height Tapered

Cat. No. CRL9040S18 18mm Collar Height Tapered

Cat. No. CRL9040S23 23mm Collar Height Tapered

CAT. No. CRL9040S28 28mm Collar Height Tapered

Cat. No. CRL9040S33 33mm Collar Height Tapered

33

t: 00 800 0421 6144 door hardware and office partition systems e: crl@crlaurence.co.uk w: crlaurence co uk

CRL Jackson® Heavy-Duty Floor Mounted Door Closer



Jackson® 900 Series Heavy-Duty Floor Mounted Door Closers Basic Package

- · Multi-size spring power adjustable
- Interchangeable spindle heights
- 453.5kg max weight
- 1370mm max door width
- · Leveling and door centering adjustments
- BS EN1154 Classification 3.8.6/1.1.1.3
- Spindle and cover plate to be purchased separately
- 10 year limited warranty

Basic Package consists of: 990 closer body, cement case and installation tool package

Cat. No. J993H0D

90°/120° Basic Package Closer, Hold Open

Cat. No. J994H0D

105° Basic Package Closer, Hold Open

Cat. No. J990NH0D Basic Package Closer, No Hold Open

Cat. No. J995BCD

180° Basic package Closer with Backcheck at 85°, No Hold Open

VARIABLE **CLOSING SPEED**

VARIABLE **POWER**

OPTIONS

Jackson® 900 Series Heavy-Duty Floor Closer Cover Plate

- Fits 900 Series floor mounted door closers
- · Allows for full closer adjustment without removing door

Cat. No. EUJ7020CPBS

Cat. No. EUJ7020CPPS



Interchangeable Floor Closer Spindles

- For use with CRL floor mounted closers
- For use with DORMA® BTS75 Series floor mounted door closer
- For use with Jackson® 900 Series floor mounted door closer
- Seven available heights from 3 to 33mm
- · Flat tapered type
- For use with all CRL floor springs

Cat. No. CRL9040S3

3mm Collar Height Tapered

Cat. No. CRL9040S8 8mm Collar Height Tapered

Cat. No. CRL9040S13

13mm Collar Height Tapered Cat. No. CRL9040S18

18mm Collar Height Tapered

Cat. No. CRL9040S23

23mm Collar Height Tapered

CAT. NO. CRL9040S28

28mm Collar Height Tapered

Cat. No. CRL9040S33

33mm Collar Height Tapered

CRL Dorma® Heavy-Duty Floor Mounted Door Closer



Dorma® BTS80 Heavy-Duty Series **Floor Mounted Door Closers**

- Interchangeable spindle heights
- · 299kg max weight
- 1372mm max door width
- Selective multi-point hoold open position
- · Variable delayed action
- UL listed
- · Cover to be purchased separately
- 25 year limited warranty

VARIABLE **CLOSING SPEED**

VARIABLE DELAYED ACTION

SELECTIVE MULTI-POINT HOLD OPEN POSITION

Cat. No. BTS802

- Size 2 (FN4)
- Interior Door Width Capacity: 762 to 1219mm • Exterior Door Width Capacity: 762 to 1067mm

Cat. No. BTS803

- Size 3 (EN6)
- Interior Door Width Capacity: 1219 to 1372mm
- Exterior Door Width Capacity: 1067 to 1219mm

Cat. No. BTS80BF

- ADA, 8.5lbs (3.85kg)
- Exterior Door Width Capacity: 914mm

OPTIONS

Dorma® BTS80 Series Floor Closer Cover Plate

- Fits Dorma® BTS80 Series floor mounted closer
- Universal design, suitable for left and right hand applications
- · Allows for full closer adjustment without removing the door



Polished Stainless



Interchangeable Floor Closer Spindles

- For use with DORMA® BTS75 Series floor mounted door closer
- For use with CRL floor mounted closers
- For use with Jackson® 900 Series floor mounted door closer
- Seven available heights from 3 to 33mm
- Flat tapered type
- For use with all CRL floor springs


3mm Collar Height Tapered Cat. No. CRL9040S8 8mm Collar Height Tapered Cat. No. CRL9040S13 13mm Collar Height Tapered Cat. No. CRL9040S18 18mm Collar Height Tapered Cat. No. CRL9040S23 23mm Collar Height Tapered CAT. NO. CRL9040S28 28mm Collar Height Tapered Cat. No. CRL9040S33

33mm Collar Height Tapered

Cat. No. CRL9040S3







t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk w: crlaurence.co.uk

OUR HIGHLY EXPERIENCED TECHNICAL SUPPORT DEPARTMENT PROVIDES THE HIGHEST LEVELS OF CUSTOMER SERVICE. NEVER HESITATE TO CALL FOR FURTHER DETAILS. FREEPHONE 00 800 0421 6144



Single door with manual top and bottom pivots



Single door with floor closer



Single door with concealed overhead closer



Single door and sidelite wih top and bottom manual pivots



Single door and sidelite with floor closer



Single door and sidelite with concealed overhead closer



Single door and transom with top and bottom manual nivots



Single door and transom with floor closer



Single door, transom and Sidelite with top and bottom manual pivots



Single door, transom and sidelite with floor Closer



Single door, transom and sidelites with top and bottom manual pivots



Single door, transom and sidelites with floor closer



Paired doors with top and bottom manual pivots





Paired doors with concealed overhead closers



Paired doors and transom with top and bottom manual pivots




Paired doors and transom with floor closers




Paired doors, transom and sidelite with top and bottom manual pivots


38



Paired doors, transom and sidelite with floor closers



Paired doors transom and sidelites with top and bottom manual pivots



Paired doors, transom and sidelites with floor closers



Top Door Patch Fitting with 1NT303 Insert • 65mm pivot setback

- · High density cast body
- For use with free swing top pivot/retractable pivots
- For 10 or 12mm glass

Cat. No. PH21ABS Brushed Stainless Cat. No. PH21APS Polished Stainless





Top Door Patch Fitting with 1NT304 Insert

- 65mm pivot setback
- · High density cast body
- For use with overhead concealed closers square spindle
- For 10 or 12mm glass

Cat. No. PH21BBS **Brushed Stainless** Cat. No. PH21BPS





Adjustable European Top Door Patch Fitting

- 65mm pivot setback
- Adjustable pivot insert allows three degrees movement for proper door alignment
- For use with overhead concealed closers square spindle

Cat. No. PH21CBS **Brushed Stainless**

Cat. No. PH21CPS

• For 10 or 12mm glass





Bottom Door Patch with 1NT301 Insert

- 65mm pivot setback
- For use with floor closer or bottom free swing pivots
- For 10 or 12mm glass

Cat. No. PH11CBS Brushed Stainless

Cat. No. PH11CPS Polished Stainless





Bottom Door Patch With 1NT302 Insert

- 65mm pivot setback
- For use with square style spindle Casma floor closers or 1NT404 pivot - see page 45
- For 10 or 12mm glass

Cat. No. PH11DBS Brushed Stainless

Cat. No. PH11DPS Polished Stainless



t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence co uk



Wall Mounted Transom Patch With 1NT300 Insert

 Works with both 70 and 65mm pivot setback door patch fittings









Sidelite Transom Patch With 1NT300 Insert

- · Works with both 70 and 65mm pivot setback door patch fittings
- For 10 or 12mm glass

Cat. No. PH40BS Brushed Stainless

Cat. No. PH40PS Polished Stainless



Patch Fitting Replacement Cover Plate for PH11 and PH21

• For PH11, and PH21 patch fittings - see page 39

Cat. No. 1NT101BS Brushed Stainless

Cat. No. 1NT101PS Polished Stainless





Cat. No. 1NT102BS

Cat. No. 1NT102PS





• For PH40 sidelite mounted transom patch fittings - see above

Cat. No. 1NT103BS

Cat. No. 1NT103PS



40







Left Hand Sidelite Transom Patch with Support Fin Bracket and 1NT300 Insert

- Works with both 70 and 65mm pivot setback door patch fittings
- For 10 or 12mm glass

Cat. No. PH41LBS **Brushed Stainless**

Cat. No. PH41LPS Polished Stainless





Right Hand Sidelite Transom Patch with Support Fin Bracket and 1NT300 Insert

- Works with both 70 and 65mm pivot setback door patch fittings
- For 10 or 12mm glass

Cat. No. PH41RBS Brushed Stainless

Cat. No. PH41RPS

Polished Stainless





90 Degree Left Hand Sidelite Patch with 1NT300 Insert

- 65mm pivot setback door patch fittings
- For 10 and 12mm glass

Cat. No. PH42LBS Brushed Stainless

Cat. No. PH42LPS Polished Stainless





90 Degree Right Hand Sidelite Patch with 1NT300 Insert

- 65mm pivot setback door patch fittings
- For 10 and 12mm glass

Cat. No. PH42RBS **Brushed Stainless**

Cat. No. PH42RPS Polished Stainless



1NT300 insert (included)





- Works with both 70mm and 65mm pivot setback door patch fittings
- · High density cast body
- For 10 or 12mm glass

Cat. No. PH51BS **Brushed Stainless**

Cat. No. PH51PS Polished Stainless



t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk






Ceiling Mounted Support Fin Bracket Patch Fitting

• For 10 or 12mm glass

Cat. No. PH94BS Brushed Stainless

Cat. No. PH94PS





Corner Patch Lock

- · Euro profile cylinders to be ordered separately
- For 10 or 12mm glass

Steel Centre Patch Lock

For 10 or 12mm glass

· Euro profile cylinders to be ordered separately

Cat. No. EUR005BS Brushed Stainless Cat. No. EUR005PS


Cat. No. EUR006BS Brushed Stainless

Cat. No. EUR006PS

Polished Stainless

Polished Stainless






Transom Mounted Patch Connector with Support Fin Bracket

• For 10 or 12mm glass

Cat. No. PH71BS Brushed Stainless

Cat. No. PH71PS Polished Stainless





4-Way Patch Connector

- · Used for joining a four lite glass junction
- For 10 or 12mm glass

Cat. No. PH80BS **Brushed Stainless**

Cat. No. PH80PS Polished Stainless





4-Way Patch Connector With Support Fin Bracket

- Used for joining a four lite glass junction that needs extra support to achieve the required structural strength
- For 10 or 12mm glass

Cat. No. PH81BS **Brushed Stainless**

Cat. No. PH81PS Polished Stainless




Centre Patch Lock Keeper

- To be used with EUR006
- For 10 or 12mm glass

Cat. No. EUR006KBS Brushed Stainless

Cat. No. EUR006KPS





Sidelite Mounted Transom Patch with Reversible Door Stop and 1NT310 Insert

- Used to connect a sidelite and transom together
- · Doors can swing either in or out

Cat. No. PH60BS **Brushed Stainless**

Cat. No. PH60PS Polished Stainless

Cat. No. PH70BS

Cat. No. PH70PS

Polished Stainless

Brushed Stainless

For 10 or 12mm glass



PTH Series Glass Mounted Patch Lock


- Includes a machined body, lock mechanism complete with keyed cylinder, finished cover plates, and gaskets for 10 and 12mm glass
- Lock is supplied with three keys and finished strike plate
- For 10 or 12mm glass

Cat. No. PTH25BS Brushed Stainless

Cat. No. PTH25PS Polished Stainless



42



Transom Mounted Connector with Two Reversible Door Stop and 1NT310 Insert

- CRL door stops can be set for the doors to only open in or out
- You can also make it so one door opens in and the other door opens out.
- The connector can be used on one lite or two lite transoms, and with the stops removed can be used as a connector only.
- Doors can swing either in or out
- For 10 or 12mm glass



43

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems



Keyed Extended Length Cylinder Lock with Thumbturn

- For use with PTH311 Series lever latch (see page 58) installation and euro style patch locks EUR005 and EUR006 - see page 43
- Available in several finishes
- 60mm length

Cat. No. EC3BS **Brushed Stainless**

Cat. No. EC3PS Polished Stainless

Cat. No. EC3BSKA Keved Alike. Brushed Stainless

Cat. No. EC3PSKA

Keyed Alike, Polished Stainless



Adjustable Free-Swinging Floor Pivot with Tapered Flat Spindle

- · Flat tapered spindle
- 100kg capacity
- Provides 6mm height adjustment
- Requires 22 to 25mm diameter hole

Cat. No. 1NT406



Keyed Extended Length Cylinder/Cylinder

- For use with PTH311 Series lever latch (see page 58) installation and euro style patch locks EUR005 and EUR006 - see page 43
- Available in cylinder/thumbturn and cylinder/cylinder
- 60mm length

Cat. No. EC5BS Brushed Stainless

Cat. No. EC5PS

Cat. No. EC5BSKA Keved Alike. Brushed Stainless

Cat. No. EC5PSKA Keved Alike, Polished Stainless



Adjustable Free-Swinging Floor Pivot with Tapered Square Spindle

- · Square tapered spindle
- . 100kg capacity
- · Provides 6mm height adjustment
- Requires 22 to 25mm diameter hole

Cat. No. 1NT404



Top Center-Hung Free Swing Pivot

- Surface mount top pivot for use with with CRL patch fittings see page 16
- Installs easily to wood or metal substrates

Cat. No. 1NT401

Cat. No. 1NT402

Cat. No. 1NT403

Header Mounted Top Free Swinging Pivot

- For use with top door patch fittings
- Mounts in masonry or metal header

Cat. No. 1NT405



Walking Beam Top Pivot

- For centre-hung applications when using a concealed floor mounted door closer or free swinging top pivot
- Optional cover plates available in several finishes
- For use with WEDGE-LOCK® Door Rail System see page 50

Cat. No. CRL9040WBP



Floor Mounted Bottom Free-Swinging Pivot

- 22mm flat tapered spindle
- 200kg capacity
- To be used with CRL patch fittings



Walking Beam Top Pivot Cover Plate

- Used to cover and conceal the CRL walking beam top pivot screws
- Other finishes available
- For centre-hung applications when using a concealed floor mounted door closer

Cat. No. CRL9040CPBS

Cat. No. CRL9040CPPS

45



44

Adjustable Free-Swinging Floor Pivot

- For use with our low profile door rails PH11C and CRL bottom patch fittings - see page 39
- 100kg capacity
- 9.5mm minimum clearance
- Can be floor or threshold mounted
- 5mm height adjustment
- · Aluminum in colour



t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk



Adjustable Top Door Patch Insert for Use with 15mm Diameter Top Pivot Pin

- For use with PH21 top door patch fitting see page 39
- Suitable for use with top pivot diameters of 15mm

Cat. No. 1NT303

Strike Plate

- Works with EDR door rails with locks see page 50
- For use with EUR005 lock see page 43

Cat. No. 777SPBS Brushed Stainless





Transom Patch Door Stop Insert

• For use with PH34, PH40, PH41L, PH41R, PH42L, PH42R and PH51 transom patch fittings to create a door stop - see pages 39 to 41

Cat. No. 1NT306



Dust Proof Keeper

Accepts a 16mm diameter plunger bolt

Cat. No. AMR207BN Brushed Nickel

Cat. No. AMR207PS Polished Stainless



Cat. No. EUR208PS



• For use with EUR005 patch lock - see page 43



Dust Proof Keeper

- Available in locking and non-locking models
- Accepts 16mm diameter plunger bolt

Cat. No. AMR208BN Locking, Brushed Nickel

Cat. No. AMR208PS Locking, Polished Stainless

Cat. No. AMR209BN Non-locking, Brushed Nickel

Cat. No. AMR209PS Non-locking, Polished Stainless

Transom Patch Keeper Insert for EUR005 Lock

- For use with PH34, PH40, PH41L, PH41R, PH42L, PH42R and PH51 transom patch fittings to create a door stop - see pages 39 to 41
- Transom patch fittings to create a keeper for the AMR205 lock

Cat. No. AMR305



• For use with PH60 mounted transom patch fitting and PH70 mounted transom connector - see page 42

Cat. No. 1NT310



Header Mounted Single Door Stop

- Turns double acting door into single acting one-way door
- · Provides positive stop
- Available for single and double doors

Cat. No. 1NT307BS Brushed Stainless

Cat. No. 1NT307PS





Header Mounted Double Door Stop

- Turns double acting door into single acting one-way door
- Provides positive stop
- Available for single and double doors

Cat. No. 1NT308BS

Cat. No. 1NT308PS

47

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems



CRL Door Rails and Side Rails

This section includes the patented WEDGE-LOCK® Door Rail Systems with Kwik-Adjust™ pivot alignment system which allows the installer to quickly and easily adjust the lateral alignment of the pivot centres by simply turning a single screw in either the top or bottom rail of the door.



CRL Door Rails and Side Rails



Door Rail 102mm Square Custom Length Without Lock

- Patented WEDGE-LOCK® Door Rail System
- Kwik-Adjust™ pivot alignment system
- · Adjust and align doors without removal
- Pivot arms to be ordered separately
- Top or bottom rails
- 1250mm max length
- For 10 or 12mm 'all glass doors'

Cat. No. EDR4SBS38

10mm glass, Brushed Stainless

Cat. No. EDR4SPS38

10mm glass, Polished Stainless

Cat. No. EDR4SBS12

12mm glass, Brushed Stainless

Cat. No. EDR4SPS12

12mm glass, Polished Stainless

Compatible with CRL floor springs see page 28



Door Rail 102mm Square Custom Length With Lock

- Patented Wedge-Lock® glass securing system
- Kwik-Adjust[™] pivot alignment system
- · Adjust and align doors without removal
- Pivot arms and cylinder to be ordered separately
- 1250mm max length
- For 10 or 12mm 'all glass doors'

Cat. No. EDR4SBS38L

10mm glass, Brushed Stainless

Cat. No. EDR4SPS38L

10mm glass, Polished Stainless

Cat. No. EDR4SBS12L

12mm glass, Brushed Stainless

Cat. No. EDR4SPS12L

12mm glass, Polished Stainless

Compatible with CRL floor springs see page 28

Cut to length and manufactured from stock from CRL UK. Fast Turnaround



Low Profile Door Rail 59mm Square Custom Length Without Lock

- Patented WEDGE-LOCK® Door Rail System
- Kwik-Adjust™ pivot alignment system
- · Adjust and align doors without removal
- · Pivot arms to be ordered separately
- Top or bottom rails
- 1250mm max length
- · For 12mm 'all glass doors'

Cat. No. EDR2SBS12

12mm, Brushed Stainless

Cat. No. EDR2SPS12

12mm, Polished Stainless

NEW



Low Profile Door Rail 59mm Square Custom Length With Lock

- Patented WEDGE-LOCK® Door Rail System
- Kwik-Adjust™ pivot alignment system
- Adjust and align doors without removal
- Pivot arms to be ordered separately • Top or bottom rails
- 1250mm max length
- For 12mm 'all glass doors'

Cat. No. EDR2SBS12L

Cat. No. EDR2SPS12L

12mm, Polished Stainless

NEW



Bottom Low Profile Pivot Insert

- For use with FDR2 door rails
- Accepts flat tapered floor closer spindle or universal round free-swing floor spindle
- For use with 1NT402, 1NT403 and 1NT406 bottom pivots only see page 44 and 45

Cat. No. 1NT701



Top Low Profile Pivot Insert for 15mm Diameter Spindle

- For use with EDR2 door rails
- Accepts overhead pivot with 15mm diameter spindle
- For use with 1NT401 or CRL9040WBP top pivots see page 44 and 45

Cat. No. 1NT703



Cat. No. 1NT704




50

- Accepts overhead closer with 14 mm square spindle
- For use with 1NT402, 1NT403 and 1NT406 bottom pivots only see page 44 and 45



Slimline Door Rail 35mm Without Lock

- · For interior use only
- 25mm width
- For 12mm glass



Slimline Door Rail 35mm With Lock · For interior use only • 25mm width

Cat. No. SP35BS12SL **Brushed Stainless**

Cat. No. SP35PS12SL

Bottom Pivot Insert

· For 12mm glass

- For use with SP door rails see above
- Accepts flat tapered floor closer spindle or universal round free-swing floor spindle

Cat. No. 1NT801

- Top Pivot Insert • For use with SP door rails - see above
- For use with 1NT401 or CRL9040WBP see page 44 and 45

Cat. No. 1NT803



Top Closer Insert

- . For use with SP door rails see above
- . For use with overhead concealed closers



Cat. No. 1NT804

51

t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence co uk

CRL Pivot Arms

Short Center-Hung Floor Closer Arm

- Arms for floor mounted door closers with flat tapered spindles see page 32
- Designed to work with WEDGE-LOCK® Door Rail System see page 50
- . For CRL door rail type gates



Cat. No. CRL9040AS

Cat. No. CRL9040TDF

Standard Top Door Rail Pivot Arm

- Standard models for center-hung applications
- Work with free-swinging and walking beam pivots
- 15mm diameter pin

Heavy-Duty Top Door Rail Pivot Arm

- Heavy-duty models for center-hung applications
- Fits 15mm diameter pin

Cat. No. CRL9060TDF

CRL Adjustable End-Load Floor Mount Bottom Pivot Set

- · Adjustable without removing the door
- Bottom clearance adjustable from 1/4" to 1/2" (6 to 12 mm)
- · For use with end-load arm applications



52

Cat. No. CRL8010ADJ

CRL Lock Accessories



Keyed Extended Length Cylinder/Cylinder

- Works on PTH311 Series lever latch (see page 58) installation and euro style patch locks, EUR005 and EUR006 see page 43
- Available in cylinder/thumbturn and cylinder/cylinder
- 60mm length

Cat. No. EC5BS

Brushed Stainless

Cat. No. EC5PS Polished Stainless

Cat. No. EC5BSKA Keyed Alike, Brushed Stainless

Cat. No. EC5PSKA Keyed Alike, Polished Stainless

Strike Plate

- Works with EDR door rails with locks see page 50
- For use with EUR005 lock see page 43



Cat. No. 777SPBS

Cat. No. 777SPPS

Polished Stainless

Dust Proof Keeper

Accepts a 16mm diameter plunger bolt

Cat. No. AMR207BN Brushed Nickel

Cat. No. AMR207PS

Polished Stainless

Dust Proof Keeper

- · Available in locking and non-locking models
- Accepts 16mm diameter plunger bolt



Cat. No. AMR208BN

Locking, Brushed Nickel

Cat. No. AMR208PS

Locking, Polished Stainless

Dust Proof Keeper

- Available in locking and non-locking models
- Accepts 16mm diameter plunger bolt

Cat. No. AMR209BN Non-locking, Brushed Nickel

Cat. No. AMR209PS

Non-locking, Polished Stainless





53

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems

CRL Door Accessories

Header Mounted Single Door Stop

- . Turns double acting door into single acting one-way door
- Provides positive stop
- Available for single and double doors



Cat. No. 1NT307PS



Header Mounted Double Door Stop

- Turns double acting door into single acting one-way door
- Provides positive stop
- Available for single and double doors

Cat. No. 1NT308BS Brushed Stainless

Cat. No. 1NT308PS



Pile Weatherstrip for Single Door Rail - Set of 2

- Specially designed to help reduce air and water infiltration
- For use with EDR door rails see page 50
- Available in two finishes

Cat. No. DRWSAS

Satin Anodised 908mm Length

Cat. No. DRWSA144

Satin Anodised 3660mm Length



Satin Bright Anodised Vertical Weatherstile Kits for 12mm Glass Single Doors

- For use with EDR door rails see page 50
- Reduces drafts and protects the edge of the glass
- Works only with CRL DRS WEDGE-LOCK® Door Rail System for both single and double door applications - see page 50
- Other cladded architectural finishes available
- For 12mm glass

Cat. No. W12SAS



54

Clear Polycarbonate Wipe with Pile Weatherstrip

- · Installs without tools
- Eliminates drafts between 'all-glass' doors
- For 12mm glass doors

Cat. No. CW12

CRL Side Lite Rails



3.05m Length Square Sidelite Rails

- Vinyl provided to use with 12mm glass. Vinyl for 10mm glass to be ordered separately
- Extruded saddle is reversible to match 6 or 19mm door clearances
- Match our EDR4 Series door rails for even sightline see page 50

Cat. No. SR4SBS3812SL

Brushed Stainless

Cat. No. SR4SPS3812SL Polished Stainless



End Caps for square Sidelite Rails

- Several finishes available to match CRL sidelite rails
- For use with SR4S side rails see above
- · Heavy forged castings

Cat. No. SREC4SBS Brushed Stainless

Cat. No. SREC4SPS



3.05m Length Low Profile Sidelite Rail with Saddle

- Vinyl provided for use with 12mm glass
- Extruded saddle is reversible to match 6mm or 19mm door clearances
- Match our EDR2S Series door rails for even sightline see page 50

Cat. No. SR2SBS12SL Brushed Stainless

Cat. No. SR2SPS12SL

Polished Stainless

NEW



Brushed Stainless Low Profile Sidelite Rail Cap

- Several finishes available to match CRL sidelite rails
- For use with SR2S side rails see above

Cat. No. SREC2SBS

Cat. No. SREC2SPS

NEW



Aluminium Neoprene Setting Block for Glass

- Protects glass edge while providing rigid glass support in sidelite rails and U-channel
- Provides proper height for recommended glass coverage
- For use with SR2S and SR4S side rails see above

Cat. No. UCSB4



Roll-In EPDM Gaskets

- Dry Glaze Push-In Top Load Glazing Gasket

Cat. No. GG38100 9.5mm width

Cat. No. GG12100 12.5mm width




t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems



CRL Handles and Locks

You will find a variety of styles and sizes in CRL's range of handles and locks. From mounted latch locks and pull handles to panic exit devices, this range includes the right products to suit your needs.



CRL Handles and Locks



Glass Mounted Latch with Lock and Thumbturn

- Works on single or double doors
- Field reversible
- · Glass fabrication required
- 304 Grade stainless steel
- · Available in four finishes
- · Includes key/thumb cylinder
- For 10 or 12mm glass

NOTE: Lever handles ordered separately

Cat. No. PTH311BS

Cat. No. PTH311PS

Polished Stainless

Glass Mounted Passage Latch

- Works on single or double doors
- · Glass fabrication required
- 304 Grade stainless steel
- · Available in four finishes
- For 10 or 12mm glass

NOTE: Lever handles ordered separately

Cat. No. PTH312BS

Cat. No. PTH312PS Polished Stainless



PTH Series Glass Mounted Long Patch Lock Keeper

- Stamped body with finished cover plates
- For use with PTH311 and PTH312 glass mounted latch mechanisms see above
- Glass fabrication required
- Available in four finishes
- For 10 or 12mm glass

Cat. No. PTH314BS

Cat. No. PTH314PS

Polished Stainless



PTH Series Glass Mounted Small Patch Lock Keeper - Europe

- Stamped body with finished cover plates
- For use with PTH311 and PTH312 glass mounted latch mechanisms see above
- · Glass fabrication required
- For 10 or 12mm glass

Cat. No. PTH315BS

Brushed Stainless Cat. No. PTH315PS

Polished Stainless



58

PTH Series Tubular Style Lever Handle

- For use with PTH311 and PTH312 glass mounted latch mechanisms see above
- Other finishes available
- Available in four finishes
- Includes: hex wrench


Cat. No. PTH302BS

Brushed Stainless

Cat. No. PTH302PS







- For use with PTH311 and PTH312 glass mounted latch mechanisms see page 58
- Other finishes available
- · Available in three finishes
- Includes: hex wrench

Cat. No. PTH303BS

Cat. No. PTH303PS Polished Stainless

PTH Series Modern Style Lever Handle

- For use with PTH311 and PTH312 glass mounted latch mechanisms see page 58
- Other finishes available
- Available in three finishes
- · Includes: hex wrench

Cat. No. PTH306BS Brushed Stainless

Cat. No. PTH306PS

Polished Stainless

Office Square Latch with Cylinder

- · Designed for use on interior doors
- Matching hinges available see page 62
- Glass fabrication required
- · Complete with cylinder
- For 8 to 10mm glass

NOTE: Handles ordered separately

Office D-Latch with Cylinder

• Mathching hinges available - see page 62

Designed for use on interior doors

Glass fabrication required

· Complete with cylinder

For 8 to 10mm glass

Cat. No. FLKSBN

Brushed Nickel

Cat. No. FLKSSA

Cat. No. FLKSMBL

Matte Black

Also available as a set which includes the square latch, 2 square hinges and

handle set (see page 22).

FLKSBNSET FLKSSASET

FLKSMBLSET

Cat. No. FLKDBN

Brushed Nickel Cat. No. FLKDSA

Satin Anodised

Also available as a set which includes the D-latch, 2 D-hinges and handle set (see

page 22).

FLKDBNSET

FLKDSASET

NEW

NEW

NEW

Office Square Latch without Cylinder

Designed for use on interior doors

NOTE: Handles ordered separately

• Matching hinges available - see page 62

Office D-Latch without Cylinder

• Matching hinges available - see page 62

• Designed for use on interior doors

· Glass fabrication required

NOTE: Handles ordered separately

For 8 to 10mm glass

- · Glass fabrication required
- For 8 to 10mm glass

NOTE: Handles ordered separately

Cat. No. FLSBN Brushed Nickel

Cat. No. FLSSA Satin Anodised

Cat. No. FLSMBL

Matte Black

Also available as a set which includes the square latch, 2 square hinges and handle set (see page 22).

FLSBNSET

FLSSASET

FLSMBLSET

Cat. No. FLDBN Brushed Nickel

Cat. No. FLDSA Satin Anodised

Also available as a set which includes the D latch, 2 D-hinges and handle set

(see page 22). FLDRNSFT FLDSASET



t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence co uk

CRL Handles and Locks



- For use with our office latches see page 59
- Designed for use on interior doors

Cat. No. FLHMTSA

Cat. No. FLHMTBN

Cat. No. FLHMTMBL

Matte Black

Brushed Nickel



Striking Plate

- For use with our office latches see page 59
- Designed for use on interior doorsa

Cat. No. FSP

NEW





T-Style Door Pull Handles

- Lengths from 300mm to 1000mm
- Grade 316 Stainless Steel
- Sold per pair
- Requires 12mm diameter holes
- For 10 to 12mm glass

Cat. No. EULP30019BS

300mm Length, 19mm Diameter, 200mm Centre-to-Centre, Brushed Stainless

Cat. No. EULP30019PS

300mm Length, 19mm Diameter. 200mm Centre-to-Centre, Polished Stainless

Cat. No. EULP40019BS

400mm Length, 19mm Diameter, 250mm Centre-to-Centre, Brushed Stainless

Cat. No. EULP40019PS 400mm Length, 19mm Diameter, 250mm

Centre-to-Centre, Polished Stainless Cat. No. EULP50019BS

500mm Length, 19mm Diameter, 350mm Centre-to-Centre, Brushed Stainless

Cat. No. EULP50019PS

500mm Length, 19mm Diameter, 350mm Centre-to-Centre, Polished Stainless

Cat. No. EULP60032BS

600mm Length, 32mm Diameter. 450mm Centre-to-Centre, Brushed Stainless

Cat. No. EULP60032PS

600mm Length, 32mm Diameter, 450mm Centre-to-Centre, Polished Stainless

Cat. No. EULP100032BS

1000mm Length, 32mm Diameter, 800mm Centre-to-Centre, **Brushed Stainless**

Cat. No. EULP100032PS

1000mm Length, 32mm Diameter, 800mm Centre-to-Centre, Polished Stainless



Extra Length Ladder Style Back-to-Back Pull Handles

- Lengths from 1219mm to 2134mm
- · Extra height for eye-catching contemporary and elegant appearance
- 32mm diameter heavy wall 304 alloy stainless steel tubina
- Required 16mm diameter holes
- · Custom finishes and sizes available
- For 10 to 19mm glass or 44mm aluminium doors

Cat No 48I PRS

1219mm Length, 914mm Centre-to-Centre, Brushed Stainless

Cat. No. 48LPPS

1219mm Length, 914mm Centre-to-Centre, Polished Stainless

Cat. No. 60LPBS

1520mm Length, 1220mm Centre-to-Centre, Brushed Stainless

Cat. No. 60LPPS

1520mm Length, 1220mm Centre-to-Centre, Polished Stainless

Cat. No. 72LPBS

1829mm Length, 1520mm Centre-to-Centre, Brushed Stainless

Cat. No. 72LPPS 1829mm Length, 1520mm Centre-to-

Centre, Polished Stainless

Cat. No. 84LPBS

2134mm Length, 1830mm Centre-to-Centre, Brushed Stainless

Cat. No. 84LPPS

2134mm Length, 1830mm Centre-to-Centre, Polished Stainless

Longer screws and mid posts available. Contact technical sales for details





- Length from 254mm to 610mm
- · Complete with matching finish metal washers
- Grade 304 Stainless Steel



- and through-bolts for mounting
- Requires 16mm diameter holes
- For 10 to 19mm glass

Cat. No. CM10X10PS

254mm Length, 254mm Centre-to-Centre, Polished Stainless

Cat. No. CM12X12BS

305mm Length, 305mm Centre-to-Centre Brushed Stainless

Cat. No. CM12X12PS

305mm Length, 305mm Centre-to-Centre, Polished Stainless

Cat. No. CM10X10BS 254mm Length, 254mm Centre-to-

Centre Brushed Stainless

Centre, Polished Stainless Cat. No. CM24X24BS 610mm Length, 610mm Centre-to-

Cat. No. CM18X18BS

Centre Brushed Stainless

Cat. No. CM18X18PS

457mm Length, 457mm Centre-to-

457mm Length, 457mm Centre-to-

Centre, Brushed Stainless Cat. No. CM24X24PS

610mm Length, 610mm Centre-to-Centre, Polished Stainless



Mounted Offset Pull Handle

- Complete with matching finish metal washers and through-bolts for mounting
- Use monolithic tempered glass
- Grade 304 Stainless Steel
- Requires 16mm diameter holes · Other finishes available
- For 10 to 19mm glass

Cat. No. CD10X10BS

254mm Length, 254mm Centre-to-Centre, Brushed Stainless

Cat. No. CD10X10PS

254mm Length, 254mm Centre-to-Centre, Polished Stainless

Cat. No. CD12X12BS

305mm Length, 305mm Centre-to-Centre, Brushed Stainless

Cat. No. CD12X12PS

305mm Length, 305mm Centre-to-Centre, Polished Stainless

Cat. No. CD18X18BS

457mm Length, 457mm Centre-to-Centre, Brushed Stainless

Cat. No. CD18X18PS

Cat. No. SQ18X18BS

Centre, Brushed Stainless

Cat. No. SQ18X18PS

Centre, Polished Stainless

Cat. No. SQ24X24BS

Centre, Brushed Stainless

457mm Length, 457mm Centre-to-

457mm Length, 457mm Centre-to-

610mm Length, 610mm Centre-to-

457mm Length, 457mm Centre-to-Centre, Polished Stainless

Cat. No. CD24X24BS125 610mm Length, 610mm Centre-to-

Centre, Brushed Stainless



Glass Mounted Square Tube Style Back-to-Back Pull Handle

- · Grade 304 Stainless Steel
- Requires a 16mm diameter hole
- Other finishes available
- Extra bolts available, sold separately
- For 10 to 19mm glass

Cat. No. SQ10X10BS

254mm Length, 254mm Centre-to-Centre, Brushed Stainless

Cat. No. SQ10X10PS

254mm Length 254mm Centre-to-Centre Polished Stainless

Cat. No. SQ12X12BS

305mm Length, 305mm Centre-to-Centre, Brushed Stainless

Cat. No. SQ12X12PS Cat. No. SQ24X24PS

305mm Length, 305mm Centre-to-610mm Length, 610mm Centre-to-Centre, Polished Stainless Centre, Polished Stainless

door hardware and office partition systems



Locking Ladder Pull Handle 1250mm

- 316 grade brushed stainless steel
- European style cylinder on external handle
- Thumbturn cylinder on internal handle
- Locking bolt located at bottom on internal handle • Requires a 19mm diameter top hole and a 13mm
- . For 10 to 12mm glass

bottom hole

Cat. No. EUKL1250BS 1250mm Length, 1000mm Centre-to-Centre, Brushed Stainless





60



CRL Free Swinging Rebated Glass Door Hinges







Cat No. FHSSA



Cat No. FHSBN Brushed Nickel Cat No. FHSMBL

Matte Black









Cat No. FHDSA



Cat No. FHDMBL Matte Black



Melbourne Series Wall Mount Offset Back Plate Hinge with Cover Plate

Cat. No. MEL024CH

NEW Cat. No. MEL024BN

- Factory set for standard closing position
- Spring controlled, closing from 5°
- Using two hinges: 45kg max door weight, 762mm max door width
- For 8 to 12mm glass

NEW DESIGN WITH COVER PLATES or replacement cover plates, order MEL024CPxx



Melbourne Series 180° Glass-to-Glass Hinge

Cat. No. MEL180CH NEW

Cat. No. MEL180BN

- Factory set for standard closing position
- Spring con trolled, closing from 5°
- Using two hinges: 45kg max door weight, 762mm max door width
- For 8 to 12mm glass

For replacement cover plates, order MEL180CPxx



Victoria Series Wall Mount Full BackPlate Hinge

Cat. No. VCT037CH

Cat. No. VCT037BN

· Factory set for standard closing position

NEW

NEW

- \bullet Spring controlled, closing from 5°
- Using two hinges: 64kg max door weight, 1000mm max door width
- For 10 to 12mm glass



Victoria Series 180° Glass-to-Glass Hinge

Cat. No. VCT180CH Chrome

NEW

Cat. No. VCT180BN

- Factory set for standard closing position
- Spring controlled, closing from 5°- Using two hinges: 64kg max door weight, 1000mm max
- For 10 to 12mm glass

Plymouth Series



Plymouth Series Wall Mount Full Back Plate Hinge

Cat. No. PLY037CH Chrome

Cat. No. PLY037BN Brushed Nickel

- Factory set for standard closing position
- \bullet Spring controlled, closing from 5°
- Using two hinges: 64kg max door weight, 1000mm max door width
- For 10 to 12mm glass



180° Glass-to-Glass Hinge

Cat. No. PLY180CH Chrome

NEW

Cat. No. PLY180BN Brushed Nickel

- Factory set for standard closing position
- \bullet Spring controlled, closing from 5°
- Using two hinges: 64kg max door weight, 1000mm max door width
- For 10 to 12mm glass




Senior Prima Series Top or Bottom Mount Hinge

Cat. No. SRPPH01CH Chrome

Cat. No. SRPPH01BN Brushed Nickel

- Factory set for standard closing position
- Spring controlled, closing from 5°
- Using two hinges: 66kg max door weight, 914mm max door width
- For 12mm glass



Senior Prima Series Glass-to-Glass Mount Hinge

Cat. No. SRPPH02CH Chrome

Cat. No. SRPPH02BN

- · Factory set for standard closing position
- Spring controlled, closing from 5°
- Using two hinges: 66kg max door weight, 914mm max door width
- For 12mm glass







All finishes are available at crlaurence.co.uk





Senior Cardiff Series Top or Bottom Mount Hinge

Cat. No. SRCAR01CH

Cat. No. SRCAR01BN

• Factory set for standard closing position


- Spring controlled, closing from 5°
- · Using two hinges: 66kg max door weight, 914mm max door width
- For 12mm glass


t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence co uk





t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk w: crlaurence.co.uk





Compact-X 70 Kit with Double Softclose for Ceiling/Wall Mount for Sliding Door


- · Ceiling or wall mount sliding
- 70kg max weight
- Complete with double softclose
- 675mm min door width
- Sold as a kit
- . For 8 and 10mm glass

Cat. No. EUCRLX2BN 2m Kit, Brushed Nickel

Cat. No. EUCRLX2SA

Cat. No. EUCRLX3BN

Cat. No. EUCRLX3SA 3m Kit, Satin Anodised




Compact-X 70 Kit with Double Softclose for Ceiling Mount with Fixed Panel

- Ceiling or wall mount sliding door with fixed panel
- 70kg max weight
- Complete with double softclose
- 675mm min door width
- Sold as a kit
- For 8 and 10mm glass

Cat. No. EUCRLX2FBA 2m Kit, Bright Anodised

Cat. No. EUCRLX3FBN

Cat. No. EUCRLX3FSA



5m Sliding Top Track

- · Excludes door accessory kit
- 70kg max weight
- 675mm min door width
- For 8 and 10mm glass

Cat. No. EUCRLX5BN

With End Caps, Brushed Nickel

Cat. No. EUCRLX5SA

Cat. No. EUCRLX5FBN With Fixed Panel Glazing Pocket, Brushed Nickel

Cat. No. EUCRLX5FSA

With Fixed Panel Glazing Pocket, Satin Anodised



- Converts single sliding door systems to double doors
- 70kg max weight
- Complete with double soft close
- 675mm min door width
- Sold as a kit
- For 8 and 10mm glass

Cat. No. EUCRLXSBK1TBN

Cat. No. EUCRLXSBK1TSA




t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk

Holes field



Sliding Door Kit (Cat. No. CRL490/495)



Single slider kits (Ceiling mount illustrated)

3m Compact-X 150 Kit Wall or Ceiling mount Sliding Door

- Wall or ceiling mount sliding door
- Complete with anti-shock manual stops
- 150kg max weight
- 680mm min door width
- Sold as a kit
- For 10 to 12mm glass

Cat. No. CRL495

Cat. No. CRL490

Cat. No. CRL490BSA

Brushed Satin Anodised

Satin Anodised

Cat. No. CRL495BSA

3m Compact-X 150 Kit Wall Double Softclose for Wall or Ceiling mount Sliding Door

- Wall or ceiling mount sliding door
- Complete with double softclose
- 150kg max weight

Sold as a kit

- 1080mm min door width
- For 10 to 12mm glass

3m Compact-X 150 Kit Wall or Ceiling Sliding Door Kit inc. Sidelight (Cat. No. CRL4901/4951) mount Sliding Door with One Sidelight

- · Wall or ceiling mount sliding door with fixed panel
- Complete with anti-shock manual stops
- 150kg max weight
- 680mm min door width
- Sold as a kit
- For 10 to 12mm glass

Cat. No. CRL4901BSA

Cat. No. CRL4901

Brushed Satin Anodised

3m Compact-X 150 Kit Wall Double Softclose for Wall or Ceiling mount Sliding Door with One Sidelight Kit


- · Wall or ceiling mount sliding door with fixed panel
- · Complete with double softclose
- 150kg max weight
- 1080mm min door width
- Sold as a kit
- For 10 to 12mm glass

Cat. No. CRL4951

Cat. No. CRL4951BSA Brushed Satin Anodised



Single slider with fixed panel kits (Ceiling mount illustrated)




Syncronised bi-parting version - 110kg max weight



62 mm

Telescoping version - 110kg max weight

Synchronised bi-parting and telescoping versions are available on request





Wall Mount Single Slider Kit

Cat. No. LSWM5BS

Cat. No. LSWM5PS

- · 316 grade stainless steel Anti-lift design
- 100kg max weight
- For 10 to 12mm glass



Wall Mount Bi-Parting Slider Kit

Cat. No. LSWM6BS

Cat. No. LSWM6PS

- 316 grade stainless steel
- Anti-lift design
- 100kg max weight
- For 10 to 12mm glass



Glass Mount Single Slider Kit

Cat. No. LSGM5BS Brushed Stainless

Cat. No. LSGM5PS

- Polished Stainless · 316 grade stainless steel
- Anti-lift design
- 100kg max weight
- For 10 to 12mm glass



Single Sliding Door Glass Mount Installation Assembly

Cat. No. LSGM6BS

Cat. No. LSGM6PS

- 316 grade stainless steel
- Anti-lift design
- 100kg max weight
- For 10 to 12mm glass



Adaptor Kit for Wood Doors

Cat. No. LSWMADT

• For 35 to 45mm thickness



Top Sliding Tube Ceiling Mount Clamp

Cat. No. LS312BS Brushed Stainless



Thru-Glass Pull

Cat. No. FP214BS

- 48mm diameter hole required
- For 10 to 12mm glass



Socket Wrench Adapter Cat. No. LSSW1



Adjustable Spanner Wrench Cat. No. SW19




Universal Spanner Wrench Kit Cat. No. USW10



t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems



72



2-Panel Overhead Track Full Bi-Fold Door

- Featuring EDR4 series 101.6mm square door rails see page 50
- Panels hung from end point, minimising obstruction
- 77kg max individual panel
- 990mm max individual panel
- With or without lock

Note: Cylinders to be ordered separately - see page 53

Cat. No. ETB210BS


10mm captail G, Brushed Stainless

Cat. No. ETB210PS 10mm Glass, Polished Stainless

Cat. No. ETB212BS 12mm Glass. Brushed Stainless

Cat. No. ETB212PS

12mm Glass Polished Stainless



3-Panel Overhead Track Full Bi-Fold Door

- Featuring EDR4 series 101.6mm square doorrails see page 50
- · Panels hung from end point, minimising obstruction
- 77kg max individual panel
- 864mm max individual panel
- With or without lock

Note: Cylinders to be ordered separately - see page 53

Cat. No. ETB310BS

10mm Glass, Brushed Stainless

Cat. No. ETB310PS


10mm Glass, Polished Stainless

Cat. No. ETB312BS

12mm Glass, Brushed Stainless

iziiiii diass, bidsiicd Staiiiics

Cat. No. ETB312PS 12mm Glass, Polished Stainless



4-Panel Bi-Part Overhead Track Full Bi-Fold Door

- Featuring EDR4 series 101.6mm square door rails see page 50
- Panels hung from end point, minimising obstruction
- Maximum individual panel: 990mm/77kg
- 77kg max individual panel
- 990mm max individual panel
- · With or without lock

Note: Cylinders to be ordered separately - see page 53

Cat. No. ETB410BS

10mm Glass, Brushed Stainless


Cat. No. ETB410PS 10mm Glass, Polished Stainless

Cat. No. ETB412BS

12mm Glass, Brushed Stainless

Cat. No. ETB412PS

12mm Glass, Polished Stainless



6-Panel Bi-Part Overhead Track Full Bi-Fold Door

- Featuring EDR4 series 101.6mm square door rails see page 50
- Panels hung from end point, minimising obstruction
- 77kg max individual panel
- 864mm max individual panel
- · With or without lock

Note: Cylinders to be ordered separately - see page 53

Cat. No. ETB610BS

10mm Glass, Brushed Stainless

Cat. No. ETB610PS

10mm Glass, Polished Stainless

Cat. No. ETB612BS

12mm Glass, Brushed Stainless

Cat. No. ETB612PS 12mm Glass, Polished Stainless



Frameless Sliding Glass Door Handle

- Low projection will not interfere with sliding door action
- Other finishes available
- For 12mm glass


Cat. No. SGH8BN Brushed Nickel

Cat. No. SGH8CH

Chrome



73





t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk



Single Arm Regular Duty Wall/Fin Mount Fitting

- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 12mm

Cat. No. FMR1BS

REGULAR Cat. No. FMR1PS





Left Hand Single Arm Regular Duty Wall/ Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 12mm

Cat. No. FMR1LHBS Brushed Stainless


Cat. No. FMR1LHPS Polished Stainless
















Double Arm Regular Duty Wall/Fin Mount Fitting

- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 12mm

Cat. No. FMR2BS

Cat. No. FMR2PS





Right Hand Single Arm Regular Duty Wall/Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 12mm


Cat. No. FMR1RHBS **Brushed Stainless**


Cat. No. FMR1RHPS Polished Stainless



















Glass attachments must be ordered separately (see page 81)







Glass attachments must be ordered separately (see page 81)







Double Arm "V" Regular Duty Wall/Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 12mm


Cat. No. FMR2VBS


Cat. No. FMR2VPS













Four Arm "V" Regular Duty Wall/Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 12mm

Cat. No. FMR4BS

Cat. No. FMR4PS Polished Stainless









Single Arm Regular Duty Post Mount Fitting

- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm


Cat. No.PMR1BS Brushed Stainless


Cat. No. PMR1PS Polished Stainless





78





Glass attachments must be ordered separately (see page 81)





Single Long Arm Regular Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm




POST MOUNT Cat no. PMR1LPS Polished Stainless

REGULAR









Double Arm Regular Duty Post Mount Fitting

- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm


Cat. No. PMR2BS Brushed Stainless


Cat. No. PMR2PS

Polished Stainless











Double Arm "V" Regular Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm


Cat. No. PMR2VBS **Brushed Stainless**

Cat. No. PMR2VPS Polished Stainless











Double Arm "V" 90 Degree Regular Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm


Cat. No.. PMR2V90BS


Cat. No. PMR2V90PS














Three Arm Regular Duty Post Mount Fitting

- Complete with hardware to mount to post or column
- 316 stainless steel
- · For glass up to 12mm




Cat. No. PMR3PS












- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm




Cat. No. PMR4PS







80









Four Arm 90 Degree Regular Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 12mm


Cat. No. PMR490BS


Cat. No. PMR490PS Polished Stainless














Rigid Head Combination Glass Attachment


- 316 stainless steel
- For 10 to 12mm glass

Cat. No. RRF10BS

Cat. No. RRF10PS Polished Stainless










Swivel Head Combination Glass Attachment

- 316 stainless steel
- For 10 to 12mm glass











Cat. No. RSF10PS Polished Stainless



Glass attachments must be ordered separately (see page 81)









Left Hand Single Arm Heavy-Duty Wall/Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 27mm


Cat. No. FMH1LHBS


Cat. No., FMH1LHPS













Right Hand Single Arm Heavy-Duty Wall/Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 27mm


Cat. No. FMH1RHBS


Cat. No. FMH1RHPS













Single Arm Heavy-Duty Wall/Fin Mount Fitting

- Complete with two threaded studs and two matching cap nuts with washers
- 316 stainless steel
- For glass up to 27mm


Cat. No. FMH1BS


Cat. No. FMH1PS





82











Double Arm Heavy-Duty Wall/Fin Mount Fitting


- Complete with two threaded studs and two matching cap nuts with washers
- 316 stainless steel
- For glass up to 27mm




Cat. No. FMH2PS Polished Stainless









Double Arm "V" Heavy-Duty Wall/Fin Mount Fitting


- Complete with hardware to mount to wall or structural fin
- 316 stainless steel
- For glass up to 27mm




Cat. No. FMH2VPS











Four Arm "V" Heavy-Duty Wall/Fin Mount Fitting


- Complete with two threaded studs and four matching cap nuts with washers
- 316 stainless steel
- For glass up to 27mm





Cat. No. FMH4PS






















Grade 316 Stainless stee

Single Arm Heavy-Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm


Cat. No. PMH1BS Brushed Stainless

Cat. No. PMH1PS
Polished Stainless












Single Long Arm Heavy-Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm















84

Double Arm Heavy-Duty Post Mount Fitting

- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm

















Grade 316 Stainless steel

Double Arm "V" 90 Degree Heavy-Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm





Cat. No.PPMH2V90PS
Polished Stainless













Three Arm Heavy-Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm


Cat. No. PMH3BS
Brushed Stainless

Cat. No. PMH3PS
Polished Stainless




















Four Arm Heavy-Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm


Cat. No. PMH4BS

Cat. No. PMH4PS











4-Way Arm 90 Degree Heavy-Duty Post Mount Fitting


- Complete with hardware to mount to post or column
- 316 stainless steel
- For glass up to 27mm


Cat. No. PMH490BS Brushed Stainless


Cat. No. PMH490PS















Rigid Head Combination Glass Attachment • One fitting for either flush or surface mount installations


- Typically used only for interior applications
- Can be used with all Heavy-Duty Spider Fittings
- 316 stainless steel
- For 12 to 27mm glass



Cat. No. HRF14PS Polished Stainless











Swivel Head Combination Glass Attachment

- One fitting for either flush or surface mount installations
- Head can swivel up to 6 degrees in any direction on its ball and socket joint
- Can be used with all Heavy-Duty Spider Fittings
- 316 stainless steel
- For 12 to 27mm glass





Cat. No. HSF14BS Brushed Stainless

Cat. No. HSF14PS





- Tilts up to 6 degrees in any direction on its wall and socket joint. This allows for any stress applied to the glass to be more evenly distributed across the entire panel of glass rather than concentrating at the hole.
- 316 stainless steel
- For 32mm insulated glass




Cat. No. HS1GF14PS

Cat. No. HS1GF14BS



Brushed Stainless Heavy-Duty Exterior Swivel Fastener

- Designed for the "all glass" look
- 316 stainless steel
- For 12 to 22mm glass




















Fin Top/Bottom Shoe Fittings

- Fin Top/Bottom Shoe Fittings are used to connect the glass fins to the structure of the floor or ceiling.
- 316 stainless steel
- For 19mm glass





Cat. No. FTF12BS

For Fin Size 305 mm Brushed Stainless

Cat. No. FTF12PS

For Fin Size 305 mm Polished Stainless

Cat. No. FTF16BS

For Fin Size 406 mm Brushed Stainless

Cat. No. FTF16PS

For Fin Size 406 mm Polished Stainless

Cat. No. FTF20BS

For Fin Size 508 mm **Brushed Stainless**

Cat. No. FTF20PS

For Fin Size 508 mm Polished Stainless

Cat. No. FTF24BS


For Fin Size 610 mm Brushed Stainless


Cat. No. FTF24PS

For Fin Size 610 mm Polished Stainless

Fin Splice Fittings

- Fin Splice Fittings are used to stack multiple pieces of glass to construct extra tall fins used to stabilize the glass facade.
- 316 stainless steel
- For 19mm glass





Cat. No. FSF12BS

For Fin Size 305 mm Brushed Stainless

Cat. No. FSF12PS

For Fin Size 305 mm Polished Stainless

Cat. No. FSF16BS For Fin Size 406 mm

Brushed Stainless

Cat. No. FSF16PS For Fin Size 406 mm

Polished Stainless

Cat. No. FSF20BS

For Fin Size 508 mm Brushed Stainless

Cat. No. FSF20PS

For Fin Size 508 mm Polished Stainless

Cat. No. FSF24BS

For Fin Size 610 mm Brushed Stainless

Cat. No. FSF24PS

For Fin Size 610 mm Polished Stainless

Spider Fitting Post Adapters (Custom Length)

- Available for Round or Flat Posts
- Custom Length to Your Specifications
- 316 stainless steel

Cat. No. AMS0B112CBS Regular Duty 38 mm

Brushed Stainless


Cat. No. AMS0B112CPS Regular Duty 38 mm Polished Stainless

Cat. No. AMS0B2CPS

Heavy-Duty 51mm Polished Stainless

Cat. No. AMS0B2CBS

Heavy-Duty 51 mm Brushed Stainless



Splice Fitting for Curtainwall Fin

- Use to stabilise glass facade
- Tested to meet ASTM E283, E331, E330, AAMA 501
- Made of 316 alloy stainless steel
- For 19mm glass

NOTE: For glass fittings see page 87

Cat. No. FSFHDBS




90 Degree Corner Bracket

- Used to secure glass at 90 degree corners
- Supplied with four rigid countersunk glass connecting screws
- 316 stainless steel
- For 12mm glass

Cat. No. CBP90BS Brushed Stainless


Cat. No. CBP90PS





door hardware and office partition systems










135° Corner Bracket

- Used to secure glass at 135 degree corners
- Supplied with four rigid 135° glass connecting screws
- 316 stainless steel
- For 12mm glass






2-Way Glass/ 1-Way Wall Circular Bracket

- Used to link two inline panels of glass to a fin support behind
- Used to connect one or two inline panels to a fin support or, when split apart they can be used to connect one panel to a wall
- Supplied with two rigid countersunk glass connecting screws and one fin securing bolt
- 316 stainless steel
- For 12mm glass






4-Way Glass/ 2-Way Wall Circular Bracket

- Used to link two or four inline panels of glass to a fin support behind
- Used to connect two or four inline panels to a fin support or, when split apart they can be used to connect one or two panels to a wall
- Supplied with four rigid countersunk glass connecting screws and two fin securing bolt
- 316 stainless steel
- For 12mm glass



90





Cat. No. CBP135BS

Cat. No. CBP135PS Polished Stainless

Cat. No. CCB2BS

Cat. No. CCB2PS Polished Stainless

Cat. No. CCB4BS

Cat. No. CCB4PS

Brushed Stainless


Link Bracket


- Used to connect two 12mm inline glass panels together to reduce differential deflection
- Supplied with two glass connecting screws
- For 12mm glass



Cat. No. CLB1BS

Cat. No. CLB1PS





Stainless Steel Sex Bolt

- Countersunk head
- For use with Cat. No. FTF12, FTF16, FTF20, FTF24, FSF12, FSF16, FSF20, FSF24 (see page 88) and CLB1 (see above)
- Sold per package which contains 10 sets.
- For 12mm glass

Cat. No. M8SBSS

Brushed Stainless

Cat. No. USW10

Universal Spanner Wrench Kit

- Adjustable universal wrench
- Includes metric and fractional spanner pin sets
- Fits CRL brand Laguna Series brackets and spider fittings to glass
- Quick and efficient method of attaching or loosening spanners.







91

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk door hardware and office partition systems



CRL Glass Awning Systems

CRL Glass Awning System will give any entrance an uncomplicated, graceful look, enhancing the design of any building.

With the use of toughened laminated glass you can add a range of glass colours, textures, and special effects not available with typical monolithic glass. This compliments and enhances the design of any building.



CRL Awning Kit for Glass Canopy



- High grade 316 stainless steel for durability in even the harshest of environments.
- Complete hardware system for 13.52mm toughened laminated glass awnings
- Provides protection from the weather without obstructing the view
- Adjustable slope for most weather conditions
- All high grade 316 alloy stainless steel components for panel sizes up to 1219mm wide and 1829mm long with two rods and mounting kits
- Easy Installation

The use of eye and fork connections makes the installation of our Awning System quick and easy. The Connecting Rods are designed to make field adjustments on varying job conditions a snap. All components are 316 alloy stainless steel for durability in even the harshest of environments.

Specifications

Material: All 316 alloy stainless steel construction.


Typical Panel: 13.52mm thick toughened laminated glass comprised of 6mm toughened glass, 1.52mm interlayer, and 6mm toughened glass.

Glass Fabrication Required:

Two 16mm and two 27mm diameter holes per panel.

Ordering Tip: Though sold individually, two Connecting Rods and two Mounting Kits are required for each panel.

See ${\it crlaurence.co.uk}$ for glass fabrication details



System Components



Stainless Steel Mounts (A and B) and Pivots (C) are contained in the GAS190BS Mounting Kit. Order Connecting Rods (D) to suit panel width and application conditions. These are contained in GAS137BS, GAS145BS and GAS154BS.

NOTE: Glass panel not included.



Oval top mounting bracket and pivot for edge of glass furthest from building are connected by one of three available rod lengths. Bottom Mount and Pivot are connected to each other to support edge of glass nearest the building.

Grade 316 Stainless steel



Brushed stainless mounting kit

- High grade 316 stainless steel for durability in even the harshest of environments.
- Complete hardware system for 13.52mm toughened laminated glass awnings
- Provides protection from the weather without obstructing the view
- Adjustable slope for most weather conditions
- For panel sizes up to 1219mm wide and 1829mm long with two rods and mounting kits
- Easy installation allows an economical and elegant solution for both commercial and residential applications

Connecting Rods









1371mm (±16mm)

Brushed stainless 940mm glass awning system connecting rod for 914mm wide panels
Brushed stainless 1143mm glass awning system connecting rod for 1067mm wide panels
Brushed stainless 1372mm glass awning system connecting rod for 1219mm wide panels

Cat. No. GAS137BS
Cat. No. GAS145BS
Cat. No. GAS154BS

CRL Double Plate Glass Awning Pivot

- Fabricated from 316 alloy stainless steel
- Available in brushed or polished stainless

This CRL Double Plate Glass Awning Pivot is for use with our Glass Awning System Support Rods. The Pivot allows for two awning panels to be attached in-line using only one Tension Rod at the connection point instead of two.



Brushed stainless double plate glass awning pivot


Cat. No.GAS122BS

Cat. No. GAS190BS

- High grade 316 stainless steel for durability in even the harshest environment
- Complete hardware system for 13.52mm toughened laminated glass awnings
- Provides protection from the weather without obstructing the view
- Adjustable slope for most weather conditions
- For panel sizes up to 1219mm wide and 1829mm long with two rods and mounting kits
- Easy installation allows an economical and elegant solution for both commercial and residential applications




CRL Glass Awning Support System




- Sold as set
- AISI 304 Grade Stainless Steel
- Brushed Stainless Steel finish
- Corrosion protection class 2, DIN EN 10088
- Glass thickness range 17.52mm to 21.52mm
- Material Grade 316 Stainless Steel available on request

Set consisting of:


- 4 point fittings Ø 45mm with mounting link
- 2 upper fastening plates
- 2 lower fastening plates
- 2 tie rods with yoke
- · Without glass



Glass: laminated safety glass consisting of heat strengthened glass with quadruple foil 8/1.52/8mm or 10/1.52/10mm



* max. tie rod distance




Tie rods	Fittings	Glass thickness	Max. design load
2	4	2 x 8 mm	2.16 kN/m ²
2	4	2 x 10 mm	3.43 kN/m ²
3	6	2 x 8 mm	1.84 kN/m ²
3	6	2 x 10 mm	2.95 kN/m ²

CAT. NO.	FASTENING PLATES	DESCRIPTION	OVERHANG	TIE ROD	CANOPY SLOPE
EUGAS900BS	Rectangular	CRL Awning Kit for 900mm	800 - 900mm	Z1 (820mm) x 2 tie rods	max. 10°
EUGAS9001BS	Rectangular	CRL Half Awning Kit for 900mm	800 - 900mm	Z1 (820mm) x 1 tie rod	max. 10°
EUGAS1100BS	Rectangular	CRL Awning Kit for 1100mm	800 - 900mm	Z1 (820mm) x 2 tie rods	max. 10°
FUGAS11001BS	Rectangluar	CBI Half Awning Kit for 1100mm	1000 - 1100mm	72 (1000mm) x 1 tie rod	max 10°




CRL Awning Kit for 1300mm Projection Glass Canopy




- Sold as set
- AISI 304 Grade Stainless Steel
- Brushed Stainless Steel finish
- Corrosion protection class 2, DIN EN 10088
- Glass thickness range 21.52mm to 25.52mm
- Material Grade 316 Stainless Steel available on request


Set consisting of:

- 4 point fittings Ø 60mm with mounting link
- 2 upper fastening plates
- 2 lower fastening plates
- 2 tie rods with yoke
- · Without glass




Glass: laminated safety glass consisting of heat strengthened glass with quadruple foil 10/1.52/10mm or 12/1.52/12mm





* max. tie rod distance




Tie rods	Fittings	Glass thickness	Max. design load
2	4	2 x 10 mm	3.01 kN/m ²
2	4	2 x 12 mm	4.43 kN/m²
3	6	2 x 10 mm	2.55 kN/m²
3	6	2 x 12 mm	3.89 kN/m ²

CAT. NO.	FASTENING PLATES	DESCRIPTION	OVERHANG	TIE ROD	CANOPY SLOPE
EUGAS1300BS	Rectangular	CRL Awning Kit for 1300mm	1200 - 1300mm	Z3 (1250mm) x 2 tie rods	max. 10°
EUGAS13001BS	Rectangular	CRL Half Awning Kit for 1300mm	1200 - 1300mm	Z3 (1250mm) x 1 tie rod	max. 10°






CRL Awning Kit for 1600/2000mm Projection Glass Canopy



- Sold as set
- AISI 304 Grade Stainless Steel
- Brushed Stainless Steel finish
- Corrosion protection class 2, DIN EN 10088
- Glass thickness range 21.52mm to 25.52mm
- Material Grade 316 Stainless Steel available on request

Set consisting of:

- 4 point fittings Ø 80mm with mounting link
- 2 upper fastening plates
- 2 lower fastening plates
- 2 tie rods with yoke
- without glass



CAT. NO.	FASTENING PLATES	DESCRIPTION	OVERHANG	TIE ROD	CANOPY SLOPE
EUGAS1600BS	Rectangular	CRL Awning Kit for 1600mm	1400 - 1600mm	Z4 (1615mm) x 2 tie rods	max. 10°
EUGAS16001BS	Rectangular	CRL Half Awning Kit for 1600mm	1400 - 1600mm	Z4 (1615mm) x 1 tie rod	max. 10°
EUGAS2000BS	Rectangular	CRL Awning Kit for 2000mm	1700 - 2000mm	Z5 (2100mm) x 2 tie rods	max. 10°
FUGAS20001BS	Bectangular	CRI Half Awning Kit for 2000mm	1700 - 2000mm	75 (2100mm) x 1 tie rod	max 10°





CRL Awning Wall Mounted Brackets




- Used on flat or curved top segmented glass
- Fabricated from 304 alloy stainless steel
- Available in brushed or polished stainless
- Custom angles or 45 degree corner brackets are available on special order
- Requires 13.52mm thick toughened laminated glass

These universal wall mounted glass awning brackets have really become popular, not just for their looks but also their versatility.








CRL Glass Awning Wall Mounted Brackets

RB50FBS CRL Double Arm Fixed Fitting Set • Fabricated from 316 alloy stainless steel • Available in brushed or polished stainless






Designed for mounting to 38mm schedule 40 post, column, or flat wall.

RB50SBS RB50SPS

CRL Double Arm Swivel Fitting Set


- Fabricated from 316 alloy stainless steel
- Available in brushed or polished stainless





Swivel Fitting
Designed for segment applications. Each Swivel
Fitting is adjustable up to 8 degrees.


CRL Awning Brackets for 785mm Projection Glass Canopy




- Sold as set
- Proven static available
- AISI 304 Grade Stainless Steel
- Corrosion protection class 2, DIN EN 10088
- Glass thickness range 13.52mm to 17.52mm
- Material grade 316 stainless steel available on request

Set consisting of:

- 2 blades
- 4 point fittings Ø 60mm with yoke
- without glass



Glass: laminated safety glass consisting of heat strengthened glass with quadruple foil 6/1.52/6 mm or 8/1.52/8 mm



20	800 / 1000mm	
80	640	80/280
300		
120		
	785	_

Blades	Overhang	Glass thickness	CRL Awning Brackets for 774mm	
2	800	2 x 6 mm	1.98 kN/m²	
2	800	2 x 8 mm	4.14 kN/m²	
2	1000	2 x 6 mm	1.34 kN/m²	
2	1000	2 x 8 mm	2.70 kN/m ²	
3	800 x 2300	2 x 6 mm	1.50 kN/m² (850)	
3	800 x 2500	2 x 8 mm	2.00 kN/m² (950)	
3	1000 x 2050	2 x 6 mm	1.50 kN/m² (725)	
3	1000 x 2450	2 x 8 mm	1.50 kN/m² (925)	
** max. charact. load				

CAT. NO.	DESCRIPTION	OVERHANG	BLADE	OVERHANG	CANOPY SLOPE
EUGAB1000BS	CRL Awning Brackets for 785mm Projection Glass Canopy	Ø 60mm	785mm x 2 blades	800-1000mm	max. 3.6°
EUGAB10001BS	CRL Half Awning Kit for 785mm Projection Glass Canopy	Ø 60mm	785mm x 1 blade	800-1000mm	max. 3.6°





101

CRL Awning Single Components



YOU MAY ALSO NEED...

EUGASU

H	•
4 6	

CAT. NO.	OPTION	DESCRIPTION
EUGAS45PF	Ø 45 mm	Point fitting with link
EUGAS60PF	Ø 60 mm	
EUGAS80PF	Ø 80 mm	



EUGAS820R0D	Z1 820 mm (Small)	Tie rod with yoke
EUGAS1000R0D	Z2 1000 mm (Small)	
EUGAS1250R0D	Z3 1250 mm (Medium)	
EUGAS1615R0D	Z4 1615 mm (Large)	
EUGAS2100R0D	Z5 2100 mm (Large)	

Upper fastening plate





Rectangular



















102

EUGASWRENCH45	Ø 45 - 60 mm	Hook wrench for point fittings
EUGASWRENCH80	Ø 80 mm	








t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk



CRL Structural Standoffs and Glass Clamps


CRL's heavy-duty, point supported Glass Rail Standoff Fittings gives the installer more adjustment during installation for those tricky job site mounting conditions. The steel back plate can be fastened directly to steel, concrete, or wood substrates and shimmed as required with blocking.


CRL gives you a choice of square or D-Shaped, with flat back or radius back clamps. The clamps are the perfect solution for partitions, railings, windbreaks and countless other projects.




CRL Langle Standoffs







CRL Langle Standoffs NEW



45mm Standoff

- 45mm diameter
- 30mm long stand off base
- Metric thread
- M10 stud included
- Tested to DIN 18003-3
- 304 grade
- Salt Spray tested to DIN EN ISO 4628-2 and 4628-3
- CRL recommends ionoplast interlaver
- 22mm diameter hole required
- For use with 8 to 20mm glass


Cat. No. RS0B45BS **Brushed Stainless**

60mm Standoff

- 60mm diameter
- 30mm long stand off base
- Metric thread
- M10 stud included
- Tested to DIN 18003-3
- 304 grade
- Salt Spray tested to DIN EN ISO 4628-2 and 4628-3
- · CRL recommends ionoplast interlayer
- 26mm diameter hole required
- For use with 10 to 24mm glass

Cat. No. RS0B60BS


Brushed Stainless



45mm Adjustable Standoff

- · 45mm diameter
- 25mm to 35mm long stand adjustable off base
- Metric thread
- M10 stud included
- Tested to DIN 18003-3
- 304 grade
- Salt Spray tested to DIN EN ISO 4628-2 and 4628-3
- CRL recommends ionoplast interlayer
- 22mm diameter hole required
- For use with 16 to 24mm glass

Cat. No. RS0BA45BS



60mm Adjustable Standoff

- 45mm diameter
- 25mm to 35mm long stand adjustable off base
- · Metric thread
- M10 stud included
- Tested to DIN 18003-3
- 304 grade
- Salt Spray tested to DIN EN ISO 4628-2 and 4628-3
- · CRL recommends ionoplast interlayer
- 26mm diameter hole required
- For use with 16 to 24mm glass

Cat. No. RS0BA60BS





CRL Heavy-Duty Standoffs

These heavy-duty Rail Standoffs are designed for glass handrail or guardrail applications. The Standoff Fittings have a 44mm standard projection from the installed attachment point.





Glass Rail Standoff Base and Cap Standard 51mm Diameter Caps

- For use with 12mm and 19mm monolithic toughened glass or 13.5mm and 21.5mm laminated toughened glass using DuPont™ SentryGlas® Interlayers
- One 19mm diameter hole per fitting
- Designed for steel, wood, and concrete substrates
- Full engineering data available at crlaurence.co.uk

Cat. No. RS0B2134BS Brushed Stainless

Cat. No. RS0B2134PS

Polished Stainless





Point Supported Standoff Base and Domed Cap

- For use with 12mm and 19mm monolithic toughened glass or 13.5mm and 21.5mm laminated toughened glass using DuPont™ SentryGlas® Interlayers
- One 19mm diameter hole per fitting3rd bullet
- Designed for steel, wood, and concrete substrates 4th bullet
- Full engineering data available at crlaurence.co.uk

Cat. No. RS0B2135BS

Cat. No. RS0B2135PS





CRL Heavy-Duty Standoffs

Grade 316 Stainless stee



Glass Rail Standoff Fittings Standard 51mm Diameter Caps

- For use with 12mm and 19mm monolithic toughened glass or 21.5mm laminated toughened glass using DuPont™ SentryGlas® Interlayers
- Two 19mm diameter holes per fitting
- Full engineering data available at crlaurence.co.uk

Cat. No. RS0B20BS
Brushed Stainless

Cat. No. RS0B20PS Polished Stainless




110


Glass Rail Standoff Fittings Standard 60mm Diameter Caps


- For use with 12mm and 19mm monolithic toughened glass or 21.5mm laminated toughened glass using DuPont™ SentryGlas® Interlayers
- Two 19mm diameter holes per fitting
- Full engineering data available at crlaurence.co.uk

Cat. No. RS0B25BS

Cat. No. RS0B25PS Polished Stainless













Cat. No. EUZSFBBS

Cat. No. EUZSFBPS

Cat. No. EUZSFBZ

Cat. No. EUZSFBBN

Zinc Body

Brushed Nickel

Brushed 316 Stainless Steel

Polished 316 Stainless Steel

Grade 316 Stainless steel

Grade 316 Stainless steel

Large D Shape 42.4mm Radius Back Clamp

- Radius back for use with 42.4mm diameter posts
- For use on mezzanines, partitions, railings and windbreaks
- Steel pin included for additional glass support
- Sold individually

63mm

63mm

112

- For 8 to 12.76mm glass
- · Rubber gasket not ncluded
- Please order the following rubber gaskets to suit: CAT.NO. EUZ8G for 8mm glass CAT.NO. EUZ876G for 8.76mm glass CAT.NO. EUZ10G for 10mm glass CAT.NO. EUZ1076G for 10.76mm glass CAT.NO. EUZ12G for 12mm glass CAT.NO. EUZ1276G for 12.76mm glass



Cat. No. EUZ42RBN Brushed Nickel Zinc Body

Cat. No. EUZ42RBS Brushed 316 Stainless Steel

Cat. No. EUZ42RPS Polished 316 Stainless Steel



Large D Shape 48.3mm Radius Back Clamp

- Radius back for use with 48.3mm diameter posts
- For use on mezzanines, partitions, railings and windbreaks
- Sold individually
- For 8 to 12.76mm glass
- · Rubber gasket not included
- Please order the following rubber gaskets to suit:

CAT.NO. EUZ8G for 8mm glass CAT.NO. EUZ876G for 8.76mm glass CAT.NO. EUZ10G for 10mm glass CAT.NO. FU71076G for 10.76mm glass CAT.NO. EUZ12G for 12mm glass CAT.NO. EUZ1276G for 12.76mm glass

- Steel pin included for additional glass support



Large D Shape Flat Back Clamp

- For use on mezzanines, partitions, railings and windbreaks
- Steel pin included for additional glass support
- Sold individually
- For 8 to 12.76mm glass
- Rubber gasket not included
- Please order the following rubber gaskets to suit:

CAT.NO. EUZ8G for 8mm glass CAT.NO. FU7876G for 8.76mm glass CAT.NO. EUZ10G for 10mm glass CAT.NO. EUZ1076G for 10.76mm glass CAT.NO. EUZ12G for 12mm glass CAT.NO. EUZ1276G for 12.76mm glass





Cat. No. EUZ48RBN Brushed Nickel Zinc Body

- Cat. No. EUZ48RBS
- Brushed 316 Stainless Steel

Cat. No. EUZ48RPS Polished 316 Stainless Steel



Cat. No. EUZFBZ

Raw Zinc Finish

Cat. No. EUZFBBS Brushed 316 Stainless Steel

Cat. No. EUZFBPS Polished 316 Stainless Steel

Cat. No. EUZFBBN Brushed Nickel







Square Type Flat Back Clamp

- Sold individually
- For 8 to 10.76mm glass
- Rubber gasket not included
- Please order the following rubber gaskets to suit: CAT.NO. EUZS8G for 8mm glass CAT.NO. EUZS876G for 8.76mm glass CAT.NO. EUZS10G for 10mm glass CAT.NO. EUZS1076G for 10.76mm glass



Square Type Flat Back Clamp

• For use on mezzanines, partitions, railings and windbreaks

• Please order the following rubber gaskets to suit:

- For use on mezzanines, partitions, railings and windbreaks

- Pin not included

Sold individually

Removable pin

. For 6 to 12.76mm glass

Rubber gasket not included

CAT.NO. EUZS6G for 6mm glass CAT.NO. EUZS676G for 6.76mm glass

CAT.NO. EUZS8G for 8mm glass

CAT.NO. EUZS876G for 8.76mm glass

CAT.NO. EUZS1076G for 10.76mm glass

CAT NO FUZS10G for 10mm glass



Cat. No. EUZSFBBSL

Brushed 316 Stainless Steel

Cat. No. EUZSFBZL













• For use on mezzanines, partitions, railings and windbreaks

Side plates for use with laminated glass

Square Type Flat Back Clamp

- Safety pin included
- Sold individually
- For 6 to 12.76mm glass Rubber gasket not included
- Please order the following rubber gaskets to suit:

CAT.NO. EUZLS6GL for 6mm glass CAT.NO. EUZLS676GL for 6.76mm glass CAT.NO. EUZLS8GL for 8mm glass CAT.NO. EUZLS876GL for 8.76mm glass CAT.NO. EUZLS10GL for 10mm glass CAT.NO. EUZLS1076GL for 10.76mm glass














CRL Glass Clamp Gaskets

Cat. No. EUZLS42RBSL









Rubber gasket for EUZFB/EUZ42/EUZ48 Series Clamps

- 63mm x 45mm
- For use with toughened or laminated glass
- . Sold by the pair
- Black colour

For 10.76mm Glass Cat. No. EUZ12G

Cat. No. EUZ8G

For 8.76mm Glass

For 10mm Glass

Cat. No. EUZ876G

Cat. No. EUZ10G

Cat. No. EUZ1076G

Grade 316 Stainless steel

For 12mm Glass Cat. No. EUZ1276G

For 12 76mm Glass



55mm

55mm



114





Square Type 42.4mm Radius

Radius back for use with 42.4mm diameter posts

Side plates for use with laminated glass included

• Please order the following rubber gaskets to suit:

• For use on mezzanines, partitions, railings and windbreaks

Back Clamp

· Safety pin included

• For 6 to 12.76mm glass

CAT.NO. EUZLS6GL for 6mm glass

CAT.NO. EUZLS8GL for 8mm glass CAT.NO. EUZLS876GL for 8.76mm glass CAT.NO. EUZLS10GL for 10mm glass CAT.NO. EUZLS1076GL for 10.76mm glass CATNO FUZI S12GL for 12mm glass CAT.NO. EUZLS1276GL for 12.76mm glass

CAT.NO. EUZLS676GL for 6.76mm glass

Sold individually

- Radius back for use with 48.3mm diameter posts
- For use on mezzanines, partitions, railings and windbreaks
- Side plates for use with laminated glass included
- Safety pin included
- Sold individually
- For 6 to 12.76mm glass
- · Rubber gasket not included
- Please order the following rubber gaskets to suit: CAT.NO. EUZLS6GL for 6mm glass CAT.NO. EUZLS676GL for 6.76mm glass CAT.NO. EUZLS8GL for 8mm glass CAT.NO. EUZLS876GL for 8.76mm glass CAT.NO. EUZLS10GL for 10mm glass CAT.NO. EUZLS1076GL for 10.76mm glass
- CAT.NO. EUZLS12GL for 12mm glass





Cat. No. EUZLS48ZL













Rubber gasket for **EUZSF Series Clamps**

- 45mm x 45mm
- · For use with toughened or laminated glass
- . Sold by the pair
- · Black colour

Cat. No. EUZS8G For 8mm Glass

Cat. No. EUZS876G For 8.76mm Glass

Cat. No. EUZS10G

Cat. No. EUZS1076G

Cat. No. EUZS12G

Cat. No. EUZS1276G

Rubber gasket for EUZLSF/EUZLS42/EUZLS48 Series Clamps

- 55mm x 55mm
- For use with toughened or laminated glass
- . Sold by the pair
- · Black colour

Cat. No. EUZLS6GL

EUZLS676GL

Cat. No. EUZLS8GL

Cat. No. EUZLS876GL

For 8.76mm Glass

Cat. No. EUZLS10GL For 10mm Glass

EUZLS1076GL

For 10.76mm Glass

EUZLS12GL For 12mm Glass

EUZLS1276GL

For 12.76mm Glass

115

t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence.co.uk

CRL Glazing Accessories

Our Glass and Glazing range includes many products such as silicones, cleaners, adhesives, lifters plus many more.

We are the one-stop-shop for all your glazing tools and accessories needs.

For more choice, order your Glass and Glazing brochure.



CRL Glazing Silicone Sealants and Tools



Neutral Cure Low Modulus Glazing Silicone

- · Low odour, neutral cure formula
- Compatible with insulating glass glazing
- Excellent adhesion to most surfaces
- Low modulus
- High grade formula low shrinkage
- 300ml cartridge, 12 per case
- Special countertop display box
- Conforms to ISO 11600

Cat. No. EURTV408W White Cat. No. EURTV408BL Black Cat. No. EURTV408BR Brown Cat. No. EURTV408G Grey Cat. No. EURTV408A Anthracite

Cat. No. EURTV408R Rosewood

Cat. No. EURTV408C Clear

Cat. No. EUCCS



Crystal Clear Silicone

- · High clarity when cured
- Applications include shower enclosures and speciality glass assemblies
- 310ml cartridge
- 12 per case
- Special countertop display box

High Grade Optically Clear Silicone Sealan



Water Clear Silicone Sealant -10.3 Fluid Ounce Cartridge

- Optically clear when cured
- Applications include shower enclosures and specialty glass assemblies
- Compare our water clear silicone
- Water clear formulation for sealing glass-to-glass, glass-to-tile, and glass to u-channel

Cat. No. WCS1



Nylon Strap Frame Caulking Gun

- Smooth rod
- Lightweight, yet durable

Cat. No. GA1202



Standard Smooth Rod Caulking Gun

- Thumb pressure release button
- Our best seller is also great value
- · Perfect for low viscosity materials

Cat. No. ER3



118

CRL Sealant Finishing Tool

- Lightweight and flexible, simplifies tooling of sealants
- Titanium catalyst material will not stick to silicone or other sealants
- Measures 83mm x 89mm x 5mm

Cat. No. 55BSS

CRL Adhesives and Cleaners



Mutli-Purpose Sealant And Adhesive

- Excellent adhesion to most non-porous surfaces such as glass, quartz, ceramic, aluminium and many others
- · High quality, durable, flexible, adhesive sealant
- Based on hybrid technology for both interior and exterior applications
- Can be used safely in food preparation areas and cold storage
- · Bonds to dampsurfaces, mould resistant
- Acoustic absorbing properties
- · Paintable with most paint
- · Solvent and cyanide free
- 290ml cartridge
- Sold per box of 12

High Performance Multi-Purpose Grip and Grab Adhesiv

EG310Ultra Complete Adhesive

- · MS polymer based
- · Neutral curing and odourless
- · Cures with atmospheric moisture
- Super-fast bonding of mirrors, glass, wood, composite panels, and metal, to a range of substrates
- Free of silicone and isocyanides
- 290ml cartridge

Cat. No. EG310ULTRA

Cat. No. MSP290B

Cat. No. MSP290W

Cat. No. MSP290C

NEW

Clear -Suitable for interior use only

Cat. No. EG310



Own Label

Version Available

EG310 evergrip™ Mirror Adhesive and Painted Glass Panel Adhesive

- · Extra fast grab mirror adhesive
- · Extra strong holding capacity
- Fast curing, with skin formation in about five minutes
- · Adhesion to almost all surfaces
- · Low VOC, solvent free, low odour
- 310ml cartridge

Glass & Mirror Cleaner

. A long time favourite of the glass industry • Ammoniated formula with a pleasant aroma • Twelve big 660ml cans per case

Cat. No. EB1701 660ml can

Cat. No. EB1701A

Cat. No. 1550

119



Lint Free Glass Wipes

- New, convenient pop-up dispenser box
- Strong, four-ply white paper wipes are virtually lint-free
- Reinforced nylon scrim in both directions so they work great wet or dry
- Six pop-up boxes in each case

t: 00 800 0421 6144 e: crl@crlaurence.co.uk door hardware and office partition systems w: crlaurence co uk

S338 Sure-Grip 203mm Vacuum Lifter

- 112kg lifting capacity (safety factor 2:1)
- Greatest lifting capacity of any 203mm pump activated vacuum lifter
- One hand pump and attachment for safety when needed
- Superior "press-and-pump" attachment feature
- Built-in vacuum loss indicator
- Soft contoured sure-grip handle for comfort
- Sturdy moulded carrying case



Wood's Powr-Grip® 203mm ABS Handle Vacuum Cup

- 57kg lifting capacity
- 203mm diameter pad
- · Lightweight, heavy-duty ABS handle
- Check valve allows re-pumping without loss of remaining vacuum
- Release valve lever permits quick and complete release
- Fast attachment on smooth, non-porous flat surfaces
- Red-line indicator warns user of any vacuum loss
- Supplied with protective carrying case



Wood's Powr-Grip® 203mm Metal Handle Vacuum Lifter

- 57kg lifting capacity
- 203mm diameter pad
- Durable metal handle
- · Check valve allows re-pumping without loss of remaining vacuum
- Release valve lever permits quick, complete release
- Fast attachment on smooth, non-porous flat surfaces
- Red-line indicator warns user of any vacuum loss



Aluminium Vacuum Lifter

- 60kg lifting capacity
- 114mm diameter pads
- Sturdily built traditional design aluminium frame
- Each suction pad operates separately
- Strong, lightweight aluminium

Cat. No. 05061

Cat. No. S338

Cat. No. N4000

Cat. No. N4950

Aluminum single pad vacuum lifter

Cat. No. 05062

Aluminum double pad vacuum lifter

Cat. No. 05063

Aluminum triple pad vacuum lifter



Standard 25mm Vinyl Roller Tool

- Ideal for inserting all types of flat spline and roll-in gaskets
- Made from solid aluminium with a hard coat anodised finish
- Knurl diamond grip and a ball bearing wheel

Cat. No. VR04

280 mm standard vinyl roller tool

Cat. No. VR17

430 mm extra long vinyl roller tool

Cat. No. VR10

280 mm blue handle vinyl roller tool

CRL Handling Tools

Glasstrax Glass Dolly

- Safe glass transport with large 272kg capacity
- Self clamping action locks loads up to 50.8mm thick
- One person can load and manoeuvre





All Terrain Dolly

- · 181kg maximum capacity
- Goes where other glass dollies won't
- Heavy welded aluminum construction
- 406 mm diameter two-ply pneumatic tire
- Built-in 203 mm Wood's Powr-Grip® vacuum cup
- Includes one set of CRL RB200 roller blocks



Cat. No. ATD1



WOOD'S POWR-GRIP® D.C. Tilt Rotator Vacuum Lifting Frames

- Cord-free operation with on-board gel cell battery
- 280mm diameter lipped pads
- Multiple configurations all from the same unit
- Full 360° rotation with tilt from any position



Cat. No. EUMRTA811LDC3

NEW



LIGHTER, MORE **AFFORDÁBLE AND EVEN STRONGER!**


Introducing CRL's new 8B and 9BL Base Shoes for Frameless Glass Balustrade System

- For use with CRL TAPER-LOC® System
- 50% faster to install than alternatives
- Saves Time & Money The horizontal TAPER-LOC® design allows the system to be adjusted, dismantled and re-set
- 8B base shoes are suitable for 12mm, 15mm, and 19mm monolithic toughened glass
- 9BL base shoes are suitable for 17.52mm, 21.52mm and 25.52mm laminated toughened glass
- Stainless as standard from UK
- no need for cladding!
- Only laminated system pursuing ICC-ES approval




INNOVATIVE


EXTRUDED STRUCTURE



w: crlaurence co uk


Contact technical sales for details





Contact technical sales for a brochure or for details





Notes

t: 00 800 0421 6144 e: crl@crlaurence.co.uk w: crlaurence.co.uk

Call FREE on 00 800 0421 6144 Fax FREE on 00 800 0262 3299



Manchester
Charles Babbage Avenue Kingsway Business Park, Rochdale, OL16 4NW, England Tel: +44 (0) 1706 863 600 Fax: +44 (0) 1706 869 860 crlaurence.co.uk



Stuttgart Boschstrasse 7

D-74360 Ilsfeld

Germany Tel: +49 (0) 7062 915 93 15 Fax: +49 (0) 7062 915 93 16

crlaurence.de

Copenhagen

Stamholmen 70 Unit B,

DK-2650 Hvidovre Denmark Tel: +45 36 72 09 00

Fax: +45 36 70 33 35 crlaurence.dk



France

Boschstrasse 7 D-74360 Ilsfeld Germany

Tel: +49 (0) 7062 915 93 12 Fax: +49 (0) 7062 915 93 16

crlaurence.fr

