



Click to Print This Page



Click to Enlarge This Page

## CRL Diamond Drill Selection Chart

Feb-02

Drill Type	Diamond Type	Mounting Style	Approximate # of Holes Using a 2" Drill Bit	Fits Drill CRL Machine	Wall Thickness
<b>DCD Series</b>	Electro-Formed Diamond	Straight Shank	1500 - 2000	CRL2, 41, SDM1, PH1, PH2	.020"
<b>HBT Series</b>	Electro-Formed Diamond	Belgian	1500 - 2000	AMZ1, PDM2800	.020"
<b>PD Series</b>	Metal Bond Diamond	Straight Shank	1000 - 1500	CRL2, 41, SDM1, PH1, PH2	.045"
<b>PDT Series</b>	Metal Bond Diamond	Belgian	1000 - 1500	AMZ1, PDM2800	.045"
<b>EDD Series</b>	Diamond Plated	Straight Shank	150 - 200	CRL2, 41, SDM1, PH1, PH2	.050"
<b>AG Series</b>	Diamond Plated	Straight Shank	150 - 200	CRL2, 41, SDM1, PH1, PH2	.050"
<b>DR Series</b>	Diamond Plated	Straight Shank	125	CRL2, 41, SDM1, PH1, PH2	.050"
<b>REC Series</b>	Diamond Plated	Straight Shank	125	CRL2, 41, SDM1, PH1, PH2	.050"
<b>SRDD Series</b>	Diamond Plated	Straight Shank	50	CRL2, 41, SDM1, PH1, PH2	.040"

**Click on a Drill Series or Drill Machine to go to that page.**

All information is deemed to be accurate and current to the best of our knowledge. Information based on proper drilling technique and handling of the drill and bit. Remember, proper coolant should always be used when drilling with diamond drills. If up to date information is needed please contact CRL Technical Sales by calling Toll Free (800) 421-6144 extension 777 or by e-mail.